

**BODYSHOP** 



TAPE AND MASKING SUPPLIES

**WELDING AND SOLDERING** 



**ADHESIVES** 



**AUTOMOTIVE FLUIDS** 



SPECIALTY CHEMICALS



**SOLVENTS AND ADDITIVES** 



**OILS AND LUBRICANTS** 



**TOOLS AND SHOP ACCESSORIES** 



**PNEUMATIC ACCESSORIES** 



**HARDWARE AND REPAIR** 



**AUTOMOTIVE DETAILING** 



TIRE PRODUCTS



**LIGHTING AND ELECTRICAL** 



**MAINTENANCE** 



**HYGIENE AND SAFETY** 



**SEASONAL PRODUCTS** 



**MISCELLANEOUS** 



#### **HOOKIT™ FINISHING FILM DISC**

- High performance Aluminum Oxide cuts fast, lasts a long time, resists loading and leaves a consistent finish
- Use with a soft interface pad
- · Remove runs, dust nibs and excess orange peel from topcoat finishes before repainting or buffing
- Faster and easier to use than scuffing pads
- Appropriate for light sanding on refinish lacquer

			Backup	Interface
#	Grit	Size (in)	pad '	Pad
00907	1500	3 (7.6 cm)	05769	05771
00908	1200	3 (7.6 cm)	05769	05771
00909	1000	3 (7.6 cm)	05769	05771
00910	800	3 (7.6 cm)	05769	05771
00911	600	3 (7.6 cm)	05769	05771
00912	500	3 (7.6 cm)	05769	05771
00913	400	3 (7.6 cm)	05769	05771
00914	320	3 (7.6 cm)	05769	05771
00915	240	3 (7.6 cm)	05769	05771
00916	220	3 (7.6 cm)	05769	05771
00917	180	3 (7.6 cm)	05769	05771
00918	150	3 (7.6 cm)	05769	05771
00919	100	3 (7.6 cm)	05769	05771
00920	80	3 (7.6 cm)	05769	05771







130 ммм

#### HOOKIT™ FINISHING FILM DISC

· Use the coarser products for sanding and featheredging filler and putties, and the finer grades for further refinement and primer sanding

#	Grit	Size (in)	Interface Pad
00950	1500	6 (15.2 cm)	05774
00968	1200	6 (15.2 cm)	05774
00969	1000	6 (15.2 cm)	05774
00970	800	6 (15.2 cm)	05774
00972	500	6 (15.2 cm)	05771
00973	400	6 (15.2 cm)	05771
00975	320	6 (15.2 cm)	05771
00976	280	6 (15.2 cm)	05771
00977	240	6 (15.2 cm)	05771
00978	220	6 (15.2 cm)	05771
00979	180	6 (15.2 cm)	05771
00980	150	6 (15.2 cm)	05771
00981	120	6 (15.2 cm)	05771
00982	100	6 (15.2 cm)	05771
00983	80	6 (15.2 cm)	05771





130





#### HOOKIT™ DUST FREE FINISHING FILM DISC

- · Aluminum Oxide cuts fast, lasts a long time, resists loading and leaves a consistent finish
- Easy to remove from backup pads

#	Grit	Size (in)	Disc Pad	Interface Pad
01050	1500	6 (15.2 cm)	05865	05777
01069	1000	6 (15.2 cm)	05865	05777
01070	800	6 (15.2 cm)	05865	05777
01071	600	6 (15.2 cm)	05865	05777
01072	500	6 (15.2 cm)	05865	05777
01073	400	6 (15.2 cm)	05865	05777
01075	320	6 (15.2 cm)	05865	05777
01079	180	6 (15.2 cm)	05865	05777





130 MMM

### RED ABRASIVE STIKIT™ DISC

- Comprehensive line of economical abrasives that deliver "Best in Class" performance on a variety of substrates
- Adhesive backed Stikit™ abrasive discs allow for easy attachment and removal where DA sanding is used

#	Grit	Size (in)
01105	1500	6 (15.2 cm)
01106	1200	6 (15.2 cm)
01107	1000	6 (15.2 cm)
01108	800	6 (15.2 cm)
01109	500	6 (15.2 cm)
01110	400	6 (15.2 cm)
01111	320	6 (15.2 cm)
01112	280	6 (15.2 cm)
01113	240	6 (15.2 cm)
01114	220	6 (15.2 cm)
01104	180	6 (15.2 cm)
01115	150	6 (15.2 cm)
01116	120	6 (15.2 cm)
01117	100	6 (15.2 cm)

# PURPLE CLEAN SANDING HOOKIT™ DISC

- Extend disc life can last 2-3 times longer than traditional no-hole,
   5-hole or 6-hole discs
- Clear out more dust with less disc loading. Dust settles into the loops of the disc, and not in the air or on the disc surface
- Discs utilize the 3M<sup>™</sup> Hookit<sup>™</sup> Attachment System

#	Grit	Size (in)
01810	500	6 (15.2 cm)
01811	400	6 (15.2 cm)
01812	320	6 (15.2 cm)
01813	280	6 (15.2 cm)
01814	240	6 (15.2 cm)
01815	220	6 (15.2 cm)
01816	180	6 (15.2 cm)
01817	150	6 (15.2 cm)
01818	120	6 (15.2 cm)
01819	100	6 (15.2 cm)
01820	80	6 (15.2 cm)



130 MMM





130 MMM






#### PURPLE CLEAN SANDING HOOKIT™ DISC 334U

- Extend disc life that can last 2-3 times longer than traditional no-hole, 5-hole or 6-hole discs
- 6" (15.2 cm)

#	Grit
30760	800
30761	600






# 130 ммм

#### STIKIT™ FINISHING FILM DISC

- Designed for use in scuff sanding before painting, as well as to remove runs, dust nibs, and excess orange peel from paint and gel coat prior to compounding
- · Allows for machine sanding versus hand sanding prior to using very aggressive compounds
- Cuts fast, lasts long, resists loading and leaves a consistent finish



#### GREEN CORPS™ ROLOC™ DISC

- · For hard to reach areas in paint, rust, and weld removal
- Quick change tool for disc grinding which fits any standard 1/4 in drill or air tool

	#	Grit	Size (in)
	01396	50	2 (5.1 cm)
3M	01397	36	2 (5.1 cm)
O.V.	01398	24	2 (5.1 cm)
	01406	50	3 (7.6 cm)
130	01407	36	3 (7.6 cm)
MMM	01408	24	3 (7.6 cm)



#### STIKIT™ GOLD DISC ROLL

· Use the coarser products for sanding and featheredging filler and putties, and the finer grades for further refinement and primer sanding

#	Grit	Size (in)	Backup pad
01434	400	6 (15.2 cm)	05546, 05556, 05576
01435	320	6 (15.2 cm)	05546, 05556, 05576
01436	280	6 (15.2 cm)	05546, 05556, 05576
01437	240	6 (15.2 cm)	05546, 05556, 05576
01438	220	6 (15.2 cm)	05546, 05556, 05576
01439	180	6 (15.2 cm)	05546, 05556, 05576
01440	150	6 (15.2 cm)	05546, 05556, 05576
01441	120	6 (15.2 cm)	05546, 05556, 05576
01442	100	6 (15.2 cm)	05546, 05556, 05576
01443	80	6 (15.2 cm)	05546, 05556, 05576





ммм



#### TRIZACT™ HOOKIT™ FOAM DISCS

- Patterned, precise mineral structures for a fast cut and consistent finish every time
- Foam disc used in a spot repair system for removing P1200-P1500 grade sand scratches before using 3M™ Perfect-It™ 3000 Panel Repair System

#	Grit	Size (in)	Interface
02085	3000	6 (15.2 cm)	05777
02087	3000	3 (7.6 cm)	05771
02088	1500	6 (15.2 cm)	05777
02094	1500	3 (7.6 cm)	05771
02090	1000	6 (15.2 cm)	05777
02091	1000	3 (7.6 cm)	05771





130 MMM

#### **WETORDRY™** TRI-M-ITE™ SHEET

· Used in wet sanding, prepping and blending surrounding area

#	Grit	Size (in)
02000	600	9 × 11 (22.9 × 28 cm)
02002	400	9 x 11 (22.9 x 28 cm)
02004	320	9 × 11 (22.9 × 28 cm)
02006	240	$9 \times 11 (22.9 \times 28 \text{ cm})$
02007	220	$9 \times 11 (22.9 \times 28 \text{ cm})$
02014	180	$9 \times 11 (22.9 \times 28 \text{ cm})$
02015	150	$9 \times 11 (22.9 \times 28 \text{ cm})$
02016	120	$9 \times 11 (22.9 \times 28 \text{ cm})$
02017	100	$9 \times 11 (22.9 \times 28 \text{ cm})$
02018	80	$9 \times 11 (22.9 \times 28 \text{ cm})$



#### **WETORDRY™** SHEET

- Our fastest cutting, longest lasting abrasive for saving labor costs and improving quality
- Levels orange peel, dust nibs or paint runs in refinish acrylic lacquer paint

#	Grit	Size (in)
02045	2500	5-1/2 x 9 (14 x 22.9 cm)
02044	2000	$5-1/2 \times 9 (14 \times 22.9 \text{ cm})$
02023	1500	$5-1/2 \times 9 (14 \times 22.9 \text{ cm})$
02022	1200	$5-1/2 \times 9 (14 \times 22.9 \text{ cm})$
02021	1000	$5-1/2 \times 9 (14 \times 22.9 \text{ cm})$
02035	800	9 x 11 (22.9 x 28 cm)
02036	600	9 x 11 (22.9 x 28 cm)
02037	500	9 x 11 (22.9 x 28 cm)
02038	400	$9 \times 11 (22.9 \times 28 \text{ cm})$
02039	360	9 x 11 (22.9 x 28 cm)
02040	320	9 x 11 (22.9 x 28 cm)
02041	280	9 x 11 (22.9 x 28 cm)
02042	240	9 x 11 (22.9 x 28 cm)
02043	220	9 x 11 (22.9 x 28 cm)

### **UTILITY CLOTH SHEETS**

130 ммм

#	Grit	Size (in)
02431	Fine	9 x 11 (22.9 x 28 cm)
02432	Medium	$9 \times 11 (22.9 \times 28 \text{ cm})$
02433	Coarse	$9 \times 11 (22.9 \times 28 \text{ cm})$



130

#### PRODUCTION™ SHEETS

#	Grit	Size (in)	Paper Weight	
02115	80	9 × 11 (22.9 × 28 cm)	D	
02116	60	$9 \times 11 (22.9 \times 28 \text{ cm})$	D	
02117	50	$9 \times 11 (22.9 \times 28 \text{ cm})$	D	1 7
02118	40	$9 \times 11 (22.9 \times 28 \text{ cm})$	D	
02134	100	$2-3/4 \times 17-1/2 (7 \times 44.5 \text{ cm})$	С	<b>3</b> M
02135	80	$2-3/4 \times 17-1/2 (7 \times 44.5 \text{ cm})$	С	
02136	60	$2-3/4 \times 17-1/2 (7 \times 44.5 \text{ cm})$	С	130
02138	40	$2-3/4 \times 17-1/2 (7 \times 44.5 \text{ cm})$	С	
				МММ

# THREE-M-ITE® UTILITY CLOTH ROLL 211K

- Aluminum Oxide 211K abrasive glue-bonded to a J-weight cloth backing
- Use for general purpose work on ferrous and non-ferrous metals





#	Grit	Size
05002	320	I" × 50 yards (2.5 cm × 45.7 m)
05003	280	I" × 50 yards (2.5 cm × 45.7 m)
05004	240	I" × 50 yards (2.5 cm × 45.7 m)
05005	220	I" × 50 yards (2.5 cm × 45.7 m)
05006	180	I" × 50 yards (2.5 cm × 45.7 m)
05007	150	I" × 50 yards (2.5 cm × 45.7 m)
05008	120	I" × 50 yards (2.5 cm × 45.7 m)
05009	100	1" × 50 yards (2.5 cm × 45.7 m)
05010	80	I" × 50 yards (2.5 cm × 45.7 m)

# PRODUCTION™ RN FRE-CUT™ GOLD PAPER SHEETS

#	Grit	Size (in)	#	Grit	Size (in)
2536	800	9 x 11 (22.9 x 28 cm)	2543	240	9 × 11 (22.9 × 28 cm)
2537	600	9 x 11 (22.9 x 28 cm)	2544	220	9 x 11 (22.9 x 28 cm)
2538	500	9 x 11 (22.9 x 28 cm)	2545	180	9 x 11 (22.9 x 28 cm)
2539	400	9 x 11 (22.9 x 28 cm)	2546	150	9 x 11 (22.9 x 28 cm)
2540	360	9 x 11 (22.9 x 28 cm)	2547	120	9 x 11 (22.9 x 28 cm)
2541	320	9 x 11 (22.9 x 28 cm)	2548	100	9 x 11 (22.9 x 28 cm)
2542	280	9 × 11 (22.9 × 28 cm)	2549	80	9 x 11 (22.9 x 28 cm)





130 MMM

#### **SOFTBACK SANDING SPONGE**

- · Coated with aluminum oxide mineral
- Each grade uses a range of mineral sizes (microfine ranges from grade 1200 to 1500)

	#	Grit	Size (in)
3M	02600	Microfine	$4-1/2 \times 5-1/2 (11.4 \times 14 \text{ cm})$
	02601	Ultrafine	$4-1/2 \times 5-1/2 (11.4 \times 14 \text{ cm})$
• • • • •	02602	Superfine	$4-1/2 \times 5-1/2 (11.4 \times 14 \text{ cm})$
130	02604	Fine	$4-1/2 \times 5-1/2 (11.4 \times 14 \text{ cm})$
MMM	02606	Medium	$4-1/2 \times 5-1/2 (11.4 \times 14 \text{ cm})$





#### SCOTCH-BRITE™ GENERAL PURPOSE HAND PAD

- · For scuffing before applying paint and primer-surfacer
- · Rinses clean and does not rust

• 20 per box



130	
ммм	

#	Description
07447	Regular

Ultrafine



#### SCOTCH-BRITE™ **ROLOC™+ CLEAN AND STRIP DISC**

- Extra coarse, durable web design lasts longer and will not rust
- Maximum operating speed 8,000 RPM
- $4" \times 1/2" (10.2 \times 1.3 \text{ cm})$

#	Description
07466	Roloc+
07470	Roloc+ XT



07448



130 MMM

#### SCOTCH-BRITE™ ROLOC™ SURFACE CONDITIONING DISC

· Use for cleaning and finishing on all metals for removal of light rust, oxides and coatings

#	Grit	Size (in)
07480	Coarse	2 (5.1 cm)
07481	Medium	2 (5.1 cm)
07485	Coarse	3 (7.6 cm)
07486	Medium	3 (7.6 cm)



130 MMM



#### ROLOC™ DISC PAD **ASSEMBLY**

- Backup pad for Roloc 2" abrasive discs
- 1/4-20 INT thread
- Assembly also includes a Roloc shank and adaptor





130

#### SCOTCH-BRITE™ ROLOC™ BRISTLE DISC

- A molded, abrasive filled bristle disc instead of wire brushes for automotive use on aluminum and metal
- Use 3M holder #7500

#	Grit	Size (in)
07524	50	2 (5.1 cm)
07525	80	2 (5.1 cm)



MMM



130 **MMM** 



#### SCOTCH-BRITE™ ROLOC™ BRAKE **HUB CLEANING DISC**

- Extra Coarse
- Max: 20,000 RPM
- $1-1/2" \times 5/8" (3.8 \times 1.6 \text{ cm})$



130 ммм





#### **POWER PLUS II DEPRESSED CENTRE WHEELS**

#	Grit	Туре	Size (in)	Max. RPM
500408	A24R	27	4 × 1/4 × 5/8	15,300
500412	A36T	27	$4-1/2 \times 3/32 \times 7/8$	13,500
500415	A30R	27	$4-1/2 \times 1/8 \times 7/8$	13,500
500418	A24R	27	$4-1/2 \times 1/4 \times 7/8$	13,500
500422	A36T	27	$5 \times 3/32 \times 7/8$	12,200
500425	A30R	27	$5 \times 1/8 \times 7/8$	12,200
500428	A24R	27	$5 \times 1/4 \times 7/8$	12,200
501632	A46T	27	$6 \times 1/16 \times 7/8$	10,200
500432	A24R	27	$6 \times 1/4 \times 7/8$	10,200
500438	A24R	27	$7 \times 1/4 \times 7/8$	8,600





784 JEQ

#### **POWER PLUS II DEPRESSED CENTRE WHEELS**

#	Grit	Туре	Size (in)	Max. RPM
500711	A24R	27	4 × 1/8 × 5/8	15,300
500712	A24R	27	$4 \times 1/4 \times 5/8$	15,300
500715	A24R	27	$4-1/2 \times 1/8 \times 7/8$	13,300
500716	A24R	27	$4-1/2 \times 1/4 \times 7/8$	13,300
500719	A24R	27	$5 \times 1/8 \times 7/8$	12,300
500720	A24R	27	$5 \times 1/4 \times 7/8$	12,300
500726	A24R	27	$7 \times 1/4 \times 7/8$	8,500





784 JEQ

#### **POWER PLUS II CUT-OFF WHEELS**

• For die grinders/air cut-off tools

#	Application	Size (in)	Max. RPM
501061	Steel	3 × 1/32 × 3/8	25,461
501062	Steel	$3 \times 1/16 \times 3/8$	25,461
501063	Steel	$3 \times 3/32 \times 3/8$	25,461





#### **POWER PLUS II POWER ABRASIVE WHEEL**

For circular saws

#	Grit	Application	Size (in)	Max. RPM
501082	WA36	Acier / Inox	7 × 1/16 × 5/8	8.600





#### SUPER CHOP™ CUT-OFF WHEELS

• Fast cut, for chop saws

#	Grit	Application	Size (in)	Max. RPM
	A36	Steel		5,100
501146	A36	Steel	$14 \times 3/32 \times 1$	4,400







#### SUPER CHOP™XL CUT-OFF WHEELS

· Long life, for chop saws

#	Grit	Application	Size (in)	Max. RPM
501153		Steel	14 × 3/32 × 1	



#### **POWER ABRASIVE CUT-OFF WHEELS**

• For gas saws

#	Grit	Application	Size	Max. RPM
501220			12in × 1/8in × 20mm	6,370
501228	A24R	Steel	$14 \times 3/32 \times 1$	5,400



#### **POWERPLUS II CUT-OFF WHEELS**

• High performance, for angle grinders

#	Grit	Application	Size (in)	Max. RPM
501521	ZX60HP	Steel & Stainless	4-1/2 × .040 × 7/8	13,500
501523	ZX36HP	Steel & Stainless	$4-1/2 \times 3/32 \times 7/8$	13,500
501526	ZX60HP	Steel & Stainless	$5 \times .040 \times 7/8$	12,223
501531		Steel & Stainless		10,200
501537	ZX60HP	Steel & Stainless	$7 \times 1/16 \times 7/8$	8,500



#### **POWERPLUS TZ II CUT-OFF WHEELS**

• Premium performance, for angle grinders

#	Grit	Application	Size (in)	Max. RPI
501571	A46TZ	Steel & Stainless	4-1/2 × 3/64 × 7/8	13,500
501576	A46TZ	Steel & Stainless	$5 \times 3/64 \times 7/8$	12,220
501581	A46TZ	Steel & Stainless	$6 \times 3/64 \times 7/8$	10,200
501586	A46TZ	Steel & Stainless	$7 \times 1/16 \times 7/8$	8,500



### POWERPLUS TZ II DEPRESSED CENTRE WHEELS

• High performance, for steel

#	Grit	Application	Size (in)	Max. RPM	
501622	A46T	27	4-1/2 × 1/16 × 7/8	13,500	
501627	A46T	27	$5 \times 1/16 \times 7/8$	12,220	
501632	A46T	27	$6 \times 1/16 \times 7/8$	10,200	
501636	A46T	27	$7 \times 1/16 \times 7/8$	8,600	





#### BLENDEX™ HAND PADS

- · Pads are washable and can be reused
- Replace steel wool with no rusting, splintering or contamination of the work piece

ŵ	W	NLT	ER
		.1	Dy.
		Ŋ	147

600	
WAM	

#	Color	Size (in)
07-A100	Maroon	
07-A200	Grey	6 x 9



#### ENDURO FLEX™ ONE-STEP FINISHING DISCS

- Ultra sharp and refined zirconium grain stays sharper longer
- Special top coat to continuously cool and lubricate the disc
- · Quiet and vibration-free grinding
- Patented and trimmable backing





, o o	01.80.		Arbor	
#	Grit	Size (in)	(in)	Max RPM
15-R454	40	4-1/2	7/8	13,300
15-R456	60	4-1/2	7/8	13,300
15-R458	80	4-1/2	7/8	13,300
15-R462	120	4-1/2	7/8	13,300
15-R504	40	5	7/8	12,200
15-R506	60	5	7/8	12,200
15-R508	80	5	7/8	12,200
15-R512	120	5	7/8	12,200

# ENDURO FLEX™ REINFORCED ONE-STEP FINISHING DISCS

- Ultra sharp and refined zirconium grain stays sharper longer
- Special top coat to continuously cool and lubricate the disc
- Will not smear or contaminate the work piece
- Patented and trimmable backing with more reinforcing ribs





#	Grit	Size (in)	Arbor (in)	Max RPM
06-B454	40	4-1/2	5/8-11	13,300
06-B456	60	4-1/2	5/8-11	13,300
06-B458	80	4-1/2	5/8-11	13,300
06-B462	120	4-1/2	5/8-11	13,300
06-B504	40	5	5/8-11	12,200
06-B506	60	5	5/8-11	12,200
06-B508	80	5	5/8-11	12,200
06-B512	120	5	5/8-11	12,200
06-B604	120	6	5/8-11	10,200
06-B606	120	6	5/8-11	10,200
06-B608	120	6	5/8-11	10,200
06-B612	120	6	5/8-11	10,200

### **BLENDEX™ CONDITIONING DISCS**





#	Grit	Diameter (in)	Max RPM
04-G202	Coarse	2	30,000
04-G203	Medium	2	30,000
04-G204	Fine	2	30,000
04-G205	Super Fine	2	30,000
04-G302	Coarse	3	28,000
04-G303	Medium	3	28,000
04-G304	Fine	3	28,000
04-G305	Super Fine	3	28 000



### **TWIST™ QUICK-CHANGE SANDING DISCS**

			Diameter	•
#	Grit	Color	(in)	Max RPM
04-D203	36	Black	2	30,000
04-D205	50	Yellow	2	30,000
04-D206	60	Blue	2	30,000
04-D208	80	Orange	2	30,000
04-D210	100	Green	2	30,000
04-D212	120	Beige	2	30,000
04-D303	36	Black	3	28,000
04-D305	50	Yellow	3	28,000
04-D306	60	Blue	3	28,000
04-D308	80	Orange	3	28,000
04-D310	100	Green	3	28,000
04-D312	120	Beige	3	28,000



#### **BLENDEX™ SURFACE CONDITIONING DISCS**

#	Grit	Color	Diameter (in)	Max RPM
07-R452	Coarse	Tan	4-1/2	11,000
07-R453	Medium	Maroon	4-1/2	11,000
07-R454	Fine	Blue	4-1/2	11,000
07-R502	Coarse	Tan	5	11,000
07-R503	Medium	Maroon	5	11,000
07-R504	Fine	Blue	5	11,000



#### HP™ / HP™ COMBO SPIN-ON DISCS

#### НР™

- Ultra-durable, perfectly centered wheel
- · Grind off metal faster
- Smooth grinding with an aggressive, controlled bite

#### НР™ СОМВО

- Perfectly centered wheel
- Ideal for both cutting and light grinding work
- Holds cutting edge longer
- · Exclusive metal hub cladding

#	Grit	Туре	Diameter (in)	Thickness (in)	Arbor (in)	Max RPM
08-B400	A-24-HPS	27	4	1/4	5/8	15,000
08-B450	A-24-HPS	27	4-1/2	1/4	5/8-11 Spin	13,300
08-B460	A-24-HPS	27	4-1/2	1/4	7/8	13,300
08-B 500	A-24-HPS	27	5	1/4	5/8-11 Spin	12,200
08-B510	A-24-HPS	27	5	1/4	7/8	1,200
08-B600	A-24-HPS	27	6	1/4	7/8	10,200
08-B710	A-24-HPS	27	7	1/4	7/8	8,600
08-B452	A-30-COMBO	27	4-1/2	1/8	5/8-11 Spin	13,300
08-B462	A-30-COMBO	27	4-1/2	1/8	7/8	13,300
08-B512	A-30-COMBO	27	5	1/8	7/8	12,200
08-B602	A-30-COMBO	27	6	1/8	7/8	10,200
08-B712	A-30-COMBO	27	7	1/8	7/8	8,600
08-B701	A-24-HPS	28	7	1/4	7/8	8,600





600 WAM



#### **PIPEFITTER™ WHEELS**

- Specially formulated and reinforced for grinding joint welds between passes in pipeline construction and pipe fabrication
- Contain no iron, sulfur or chlorine (Fe, S, Cl) and will not contaminate stainless steel
- Thin for fast and free cutting and grooving
- · Can be used for cutting sheet metal

#	Grit		Thickness (in)	
08-N453	A-36-PIPE	4-1/2	3/32	7/8





### CHOPCUT™ CHOP SAW BLADES

**ALUTYPE I** • All types of aluminum and non-ferrous metals

No clogging

		Diameter	Thickness	Arbor	
#	Grit	(in)	(in)	(in)	Max RPM
	A-30-ALU		3/32	1	4,400

HIGH PERFORMANCE TYPE I • For tubing and extrusions

• Optimized for use on low power chop saws

#	Grit		Thickness (in)		Max RPM
10-P123	A-30	12	3/32		5,200
10-P143	A-30	14	3/32	1	4,400
10-P163	A-30	16	7/64	1	3,800

#### **GENERAL PURPOSE**

• Reinforced center (for solids)

#	Grit		Thickness (in)		Max RPM
10-P123	A-30	12	3/32	I	5,200
10-P143	A-30	14	3/32	1	4,400
10-P163	A-30	16	7/64	1	3,800



WALTER 600 WAM

#### PORTACUT™ CHOP SAW BLADES

· High speed cutting with gas and electric cutting saws

#	Grit	Diameter (in)	Thickness (in)		Max RPM
11-A121	A-24	12	1/8	20 mm STIHL	6,300
11-A123	A-24	12	1/8	1"	6,300
11-A141	A-24	14	1/8	20 mm STIHL	5,400
11-A143	A-24	14	1/8	["	5,400
11-D 121	C-24	12	1/8	20 mm STIHL	6,300
11-D 141	C-24	14	1/8	20 mm STIHL	5,400





600 WAM



#### ZIPTM CUTTING WHEELS

Fast and cool cutting

#	Grit	Туре	Diameter (in)	Thickness (in)	Arbor (in)	Max RPM
11-L211	A-24-ZIP		2	1/16	5/16	31,000
11-L213	A-24-ZIP	1	2	1/16	3/8	31,000
11-L302	A-60-ZIP		3	1/32	1/4	25,470
11-L312	A-24-ZIP		3	1/16	1/4	25,470
11-L303	A-60-ZIP		3	1/32	3/8	25,470
11-L313	A-24-ZIP	1	3	1/16	3/8	25,470
11-L403	A-60-ZIP	1	4	1/32	3/8	19,100
11-L413	A-24-ZIP	1	4	1/16	3/8	19,100
11-L405	A-60-ZIP	1	4	1/32	5/8	19,100
11-L415	A-24-ZIP	1	4	1/16	5/8	19,100
11-L308*	A-60-ZIP	27	3	1/32	3/8	25,470
11-L408**	A-60-ZIP	27	4	1/32	3/8	19,100





#### ZIP™ HIGH PERFORMANCE CUTTING WHEELS

- At least 40% more cuts than standard cutting wheels
- · Less friction and faster cutting

#	Grit	Туре	Diameter (in)	Thickness (in)	Arbor (in)	Max RPM
11-T042	A-60-ZIP	1	4-1/2	3/64	7/8	13,300
11-T242	A-46-ZIP	1	4-1/2	1/16	7/8	13,300
11-T052	A-60-ZIP	1	5	3/64	7/8	12,200
11-T252	A-46-ZIP		5	1/16	7/8	12,200
11-T062	A-60-ZIP	1	6	3/64	7/8	10,200
11-T072	A-30-ZIP	1	7	1/16	7/8	8,600
II-T070	A-30-ZIP		7	1/16	5/8	8,600
11-T142	A-60-ZIP	27	4-1/2	3/64	7/8	13,300
11-T453	A-46-ZIP	27	4-1/2	1/16	7/8	13,300
11-T152	A-60-ZIP	27	5	3/64	7/8	12,200
11-T503	A-46-ZIP	27	5	1/16	7/8	12,200
11-T162	A-60-ZIP	27	6	3/64	7/8	10,200





600 WAM

### ZIPTM ALU

- Thin cut-off wheels specially formulated to cut a wide variety of aluminum, aluminum alloys and non-ferrous metals without clogging
- Best wheel life and extra fast cutting in aluminum

#	Grit	Туре	Diameter (in)	Thickness (in)	Arbor (in)	Max RPM
11-U042	A-60-ZIP-ALU		4-1/2		7/8	13,300
11-U052	A-60-ZIP-ALU		5	3/64	7/8	12,200
11-U303	A-60-ZIP-ALU		3	1/32	3/8	25,470



W WALTER	600
	WAM

<sup>\*</sup>Use with 1/4» 11-L 007 mand \*\*Use with 1/4» 11-L 003 mandrel



#### MANDREL FOR ZIP™ WHEEL

#	Diameter (in)	Arbor (in)
11-L001	2	5/16
11-L004	3 & 4	3/8





#### **ALLSTEEL™ GRINDING WHEELS**

- · Heavily reinforced for absolute safety
- Fastest cutting wheel in its class
- Cool and free cutting
- Resists bending and twisting



#	Grit	Туре	Diameter (in)	Thickness (in)	Arbor (in)	Max RPM	W WALTER
08-C450	A-24-AS	27	4-1/2	1/4	7/8	13,300	
08-C455	A-24-AS	27	4-1/2	1/4	5/8-11 Metal	13,300	(00
08-C452	A-30-AS	27	4-1/2	1/8	7/8	13,300	600
08-C500	A-24-AS	27	5	1/4	7/8	12,200	WAM
08-C502	A-30-AS	27	5	1/8	7/8	12,200	
08-C600	A-24-AS	27	6	1/4	7/8	10,200	
08-C602	A-30-AS	27	6	1/8	7/8	10,200	
08-C700	A-24-AS	27	7	1/4	7/8	8,600	

#### **ALUMINUM GRINDING WHEEL**

- No clogging in any type of aluminum
- Formulated for cutting but may also be used for intermittent light grinding
- · Fast and free cutting



#	Grit	Туре		Thickness (in)	Arbor (in)	Max RPM	W WALTER
08-L450	A-24-ALU	27	4-1/2	1/4	7/8	13,300	
	A-24-ALU		-	1/4	7/8	12,200	600
08-L452	A-24-ALU	27	4-1/2	1/8	7/8	13,300	WAM

### FLEXCUT™ GRINDING WHEELS

- Deep diamond-cut pattern
- More flexibility on flat and curved surfaces
- Cooler grinding
- For ferrous and non-ferrous metals

#	Diameter (in)	Arbor (in)	Grit	Max RPM
15-L503		5/8-11	A-36-X-FLE4	12,200







#### **MOUNTED WIRE BRUSHES**

#	Туре	Diameter (in)	Width (in)	Wire (in)
13-C110	В	13/8	1/4	.008
13-C120	В	2	5/8	.0118
13-C125	В	3	3/4	.0118
13-C130	E	2 3/4	5/16	.020



#### **KNOT-TWISTED WIRE CUP BRUSHES**

- Designed for high performance brushing of large surfaces with angle grinders
- Threaded arbors
- No 13-G304 equipped with safety supporting ring for extra heavy-duty brushing and extended life





#	Diameter (in)		Wire (in)	Description
13-F304	3	5/8-11	.015	Knot -Twisted
13-G304	3	5/8-11	.020	Knot-Twisted with Ring



#### **SAUCER-CUP™ BRUSHES**

- · For angle grinders
- Built-in working angle of 45°
- · Tightly knotted for maximum impact and long brush life



WALTER	600	#	Diameter (in)		Wire (in)	Description
	WAM	13-H404	4	5/8-11		Knotted Saucer-Cup

#### **COOLCUT™ SANDING DISCS**

- For general purpose sanding, light weld removal, surface cleaning and finishing
- · High removal rate, cool cutting

#	Grit	Diameter (in)	Arbor (in)	#	Grit	Diameter (in)	Arbor (in)
15-C452	24	4-1/2	7/8	15-C502	24	5	7/8
15-C453	36	4-1/2	7/8	15-C503	36	5	7/8
15-C454	40	4-1/2	7/8	15-C504	40	5	7/8
15-C456	60	4-1/2	7/8	15-C505	50	5	7/8
15-C458	80	4-1/2	7/8	15-C506	60	5	7/8
15-C460	100	4-1/2	7/8	15-C508	80	5	7/8
15-C462	120	4-1/2	7/8	15-C702	24	7	7/8
				15-C703	36	7	7/8



WALTER	600
	WAM
7	

#### **COOLCUT™ FLAP WHEELS**

#	Grit	Diameter (in)	Width (in)	#	Grit	Diameter (in)	Width (in)
15-F054	40	1	3/8	15-F204	40	2	3/8
15-F056	60		3/8	15-F206	60	2	3/8
15-F058	80	1	3/8	15-F208	80	2	3/8
15-F062	120		3/8	15-F212	120	2	3/8
15-F154	40	1	1	15-F304	40	2	I
15-F156	60		1	15-F306	60	2	I
15-F158	80	1	1	15-F308	80	2	I
15-F162	120		1	15-F312	120	2	I
15-F004	40	1-1/2	3/8	15-F324	240	2	1
15-F006	60	1-1/2	3/8	15-F504	40	2-1/2	1-1/2
15-F008	80	1-1/2	3/8	15-F506	60	2-1/2	1-1/2
15-F012	120	1-1/2	3/8	15-F508	80	2-1/2	1-1/2
15-F104	40	1-1/2	1	15-F512	1200	2-1/2	1-1/2
15-F106	60	1-1/2	1	15-F524	240	2-1/2	1-1/2
15-F108	80	1-1/2	1	15-F704	40	3	1
15-F112	120	1-1/2	1	15-F706	60	3	I
15-F124	240	1-1/2	1	15-F708	80	3	I
				15-F712	120	3	I





#### **ABRASIVE SILICA**

- Highly aggressive abrasive Ideal for applications where tough contamination is encountered and surface removal of .0005 to .08 inches is acceptable
- Resulting finish is ideal for painting, plating and coating

#	Description	Weight
NR20-35	Coarse 20-35	22,7 kg
NR35-60	Medium 35-60	22,7 kg
NR60-80	Fine 60-80	22,7 kg





#### **ABRASIVE SILICA**

 Close graded silica sands used for sandblasting of steel, concrete or wood, for surface preparation or architectural effect, or as aggregate for mortars, grouts and concretes

Description		
10-20		
20-30		
30-60		
60-80		

44 I

THR







#### **BULL DOG® STEEL WOOL**

• 16 large pads

#	Grade
60402	#0000 Finest
60303	#000 Extra Fine
60204	#00 Very Fine
60006	#0 Fine
60013	#1 Medium
60020	#2 Coarse
60037	#3 Very Course



# SANDBLAST MEDIA GLASS BEADS

 Perfect for removing medium to light contamination without causing dimensional change, overstressing, imbedding or pitting

Description (US Screen)
30-40 (Coarse)
40-50 (Coarse)
50-70 (Med. Coarse)
70-100 (Medium)
100-170 (Fine)





# ALUMINIUM OXIDE SANDBLAST MEDIA

 Highly aggressive abrasive, for tough contamination areas

024

TMP

- 0 .0005 to 0.08 inch surface removal
- · Ideal for painting, plating and coating

#	Grit
635104	24
635106	36
635109	54
635122	100
635141	220





# JETMAG (SYNTHETIC OLIVINE PYROXENE SAND)

- · Substitute to silica sand
- Faster cleaning and reduces consumption
- Non-toxic material and environment friendly

#	Grit
635202	16-60
635203	30-60
635204	35-70
635205	120-150
635207	32





#### **SHIELD FOR HOOD**

#	Model	Description (in )
613004	RPW3	6 × 5 BH3





#### FINESSE-IT™ II MACHINE POLISH

• Entry level machine polish designed for use on OEM and fully cured automotive paints

· Removes microfine scratches and swirl marks while leaving a high gloss finish

- VOC content less than 17%
- 945 ml



# **MACHINE POLISH**

- Uniquely formulated to remove compound swirl marks
- Contains no waxes or silicones
- · Less clean up required
- 945 ml




#### PERFECT-IT™ **MACHINE POLISH**

 High-performance machine polish quickly and effectively removes compound swirl marks and produces an outstanding finish

• 945 ml



MMM



#### PERFECT-IT™ RUBBING COMPOUND

 Fast cutting rubbing compound designed remove sand scratches and leaves a fine finish on automotive paints

# Format		
06085	945 ml	
06086	3,78 L	



130 MMM



#### SUPER DUTY RUBBING COMPOUND

- Heavy cutting rubbing compound, to be used by hand or machine
- 945 ml

# 05954





#### **RUBBING COMPOUND**

- Medium cutting, liquid compound for removing 1200, 1500, and 2000 grit sanding scratches
- · Use with 3M Perfect-It Foam Compounding Pad, part number 05723

#	Format
05973	945 ml
05983	3,78 L



130 ммм



#### PERFECT-IT™ ULTRAFINE **MACHINE POLISH**

- Produces a swirl free finish even. on black vehicles
- Quickly and effectively removes fine machine polish swirls
- 945 ml



# 06068

130 MMM



#### PERFECT-IT™ 100% WOOL COMPOUNDING PAD

- 100% wool double-sided, screw-on, pad with a stiffer central hub for more cutting power
- Aggressive cut, excellent for all paints and clears
- Use with 3M™ 05710 screw-on adapter









#### PERFECT-IT™ FOAM PAD, SINGLE SIDED & FLAT BACK

• Convoluted foam face produces wheel/swirl free paint finish when used with 3M™ Perfect-It™ Machine Polish (06064 or 06065)



	#	Application	Туре	Size (in)
	05723	Compounding	Flat Back	8 (20.3 cm)
	05725	Polishing	Flat Back	8 (20.3 cm)
1	05726	Polishing	Single Sided	3 (6.6 cm)
	05737	Compounding	Single Sided	9 (22.9 cm)
	05738	Polishing	Single Sided	8 (20.3 cm)

# EZ-SAND FLEXIBLE PARTS REPAIR

- Two component flexible epoxy finishing adhesive, to repair most flexible plastic parts, including bumper covers and other plastic body panels
- 200 ml cartridge

	#	05887	5887 PLASTIC E Sent Sent E Sent E Sent Sent Sent E Sent Sent E Sent Sent E Sent Sent E Sent Sent Sent Sent E Sent Sent Sent Sent E Sent Sent Sent Sent Sent E Sent Sent Sent Sent Sent Sent Sent E Sent Sent Sent Sent Sent Sent Sent Sent
<b>3M</b>	130		Impossion or pinta Includes E7 Smill
	ммм		
7			The same of

# UNIVERSAL ADHESIVE, BLACK

130 MMM

- Two-component black urethane adhesive used as a general purpose adhesive for metal, glass and plastic
- 200 ml





#### SMC/FRP REPAIR

 Two-component epoxy adhesive with excellent sag resistance and used to bond SMC and FRP (traditional fibreglass) body panels to each other and to metal frames

• 400 ml



#### HEAVY-BODIED SEAM SEALER

- A two-part flexible seam sealer that cures quickly to a tough, strong bead for lasting seam sealing protection
- This includes door skins, floor pans, trunk floors, roof seams, and many other applications
- 200 ml



#### **FLEXIBLE FOAM**

- · Soft and flexible two-part urethane material
- Designed to replace OEM's flexible foams found on door intrusion beams, roof bows, inside body panels, pillars, and in other automotive body cavities
- Expands to 10 times its original volume
- 200 ml





### PANEL BONDING ADHESIVE

- Excellent adhesion to a wide variety of plastic and metal substrates such as cold roll steel, aluminum, SMC, and FRP
- Can be used to bond door skins, roof skins, quarter panels and box sides





#### **GENERAL TRIM ADHESIVE**

· Low VOC, clear, high strength aerosol adhesive used for bonding carpeting, jute pads, fabrics and plastics to metal and other surfaces

#	Format		
08088	475 g		
08090	539 g		



130 ммм

#### **WOODGRAIN AND STRIPE ADHESIVE REMOVER**

- · Cleans off adhesive residue after woodgrain vinyl or vinyl stripes have been removed
- 532 ml



#### **ROCKER PANEL COATING**

- Protects lower auto body panels from damage such as stone chipping
- · Textured finish
- VOC Compliant
- Gray, 590 ml

# 08889 130 SCHEMES! 250 MMM

### **HEADLIGHT LENS** RESTORATION SYSTEM

 Includes everything needed to restore two headlight lenses, excluding the user-supplied household drill (1,200-1,600 RPM), automotive tape, clean cloth, and spray bottle

# 39008



130 **MMM** 



#### SUPER FAST URETHANE

- · Medium viscosity single component moisture curing urethane adhesive, which bonds replacement auto glass to car bodies
- Black, 295 ml

# 08609 130 **MMM** 



#### **RUBBERIZED** UNDERCOATING

582 ml

# 08883



130

MMM

#### STRIP-CALK

- · A thumb-grade seam sealer for filling in joints, seams, voids and gaps
- · Soft, non-hardening butyl rubber material



#### PPS™ MIXING CUP KITS

- Replaces traditional mixing cups and filters and drastically reduces the amount of solvent required for gun cleaning
- · Liner, lid and built-in filter are all disposable, leaving only the adapter and spray gun to be
- · Allows you to clean your paint gun with as little as 3 ounces of solvent and see up to a 70% savings in cleaning solvent use
- Less operator exposure to solvents and reduction in VOCs

#	Format	Filter	
16024	L	200 microns	
16114	Mini	200 microns	
16314	Mini	125 microns	
16324	L	125 microns	





#### **BONDO-GLASS® FIBERGLASS** REINFORCED FILLER

- · Ideal for boats
- · Sands in only 20 minutes
- · Great for use on fibreglass, wood, metal, aluminum, SMC, and masonry and compatible with all paints systems
- Includes Red Cream Hardener

#	Format	
272	l quart	
bondo	939	
	BON	



#### **BONDO® BODY REPAIR KIT**

· Includes: I pint can body filler, red cream hardener, self-adhesive metal body patch and spreader





#### **BONDO® FIBERGLASS** CLOTH

 Use with Bondo® Polyester Fiberglass Resin for hundreds of repairs on cars, boats, campers, trucks, snowmobiles, tanks, etc.

#	Size	
499	8 sq. ft.	2
		bonda
		PRESIDENCE COURT TO LEADER PRINCE OF VERSED TO ADDITIONS DE MONTO
bono	939	The state of the s
	BON	



# **BONDO® BODY FILLER**

- · For use on wood, metal, aluminum, fibreglass, masonry, and concrete and compatible with all paint systems
- · Sands in 20 minutes
- Includes cream hardener

#	Format
261	l pint
262	l quart
265	I gallon





#### **BONDO® FIBERGLASS RESIN REPAIR KIT**

• Includes: Fiberglass resin, liquid hardener, plastic spreader, fiberglass cloth, mixing stick and mixing tray

#	Format	
420	1/2 pint	
422	l quart	





# 354



### **BONDO® FIBERGLASS RESIN**

- · Sandable in less than 2 hours
- · Compatible with all paints, including gel coat and marine paints. Waterproof
- Includes Liquid Hardener

#	Format
401	l pint
402	l quart
404	I gallon


bondo







#### **METAL SHEET**





290 AAS

#### **PAINT SUIT**



#### I L PAINT STRAINER

- Disposable cardboard cone with mesh inserts
- Absolute 100% straining of all paints
- Elimination of pin-hole openings no accumulation of metallics of pigments at filter tip
- Nothing is left behind in a "double meshed" or "blind spot" to throw off critical colour matching



#### **SEAM SEALER**

- Fast drying, rubber economy sealer that skins in 2 to 3 minutes
- 10,14 oz (300 ml)

#	Color
400-60	Black
400-70	Wheat





#### **URETHANE SEALER**

- Strong and flexible urethane sealer adhesive that can be applied on bare or painted metals, plastics and fibreglass
- Will not shrink Recommended for large gap filling and seams and joints that have a lot of mechanical stress, shock and vibration
- Black, 350 ml (11,85 oz)

# 400-80



333 CXF



# PREMIUM LIGHTWEIGHT BODY FILLER

- Tack free and stain resistant
- Superior spreading and sanding properties
- Advanced formula with ZNX-7 for superior adhesion to galvanized steel, aluminum, SMC and sanded OEM finishes
- · Blue cream hardener included



333 CXF

#	Format
500-10	l quart
500-20	I gallon



# QUANTUM PREMIUM LIGHTWEIGHT FILLER

- Epoxy-enriched BPO catalyst
- Contains ZNX-7™ for adhesion to galvanized steel and aluminum
- · Compatible with new HAPS-compliant and waterborne coatings
- Use with Quantum 10:1 BPO Catalyst (#455/457/458) only
- 0.5 gallon





# EVERGLASS SHORT STRAND FIBER REINFORCED FILLER

- · Contains short strand fibers and kevlar
- Prevents stress cracks in high stress areas
- Zinc compatible with ZNX-7 for adhesion and corrosion resistance over steel, galvanized steel and aluminum
- Rustproof and waterproof
- · Can be used over metal and rigid plastics



333 CXF

#	Format
500-40	l quart
500-50	l gallon



# POLYESTER GLAZING PUTTY

- Can be applied directly to bare metal, body filler, fibreglass and fully cured sanded top coats
- Contains ZNX-7™ for superior adhesion to galvanized steel, bare steel, aluminum, SMC, E-Coat and OEM finishes
- No shrinkage, easy dry
- · Reduces risk of staining
- · Blue cream hardener included



333 CXF 500-60 500-70 20 oz 1/2 gallon

Format







#### **ENGINE ENAMEL**

- · Dries to a high heat-resistant finish
- Repeated exposure up to 500°F will fuse engine enamel to the surface to increase bonding strength
- · Resistant to oil and gasoline, it will not weaken, crack, lift or peel

#	Color
300-A200	Orange
300-A204	Blue
300-A206	Universal Black
300-A211	Universal Grey
300-A216	Dark Blue



333 CXF



#### **ACRYLIC ENAMEL**

- Fast drying
- · Sprays at any angle
- 12 oz

Color
Royal Blue
Machinery Gray
Gloss Black
Gloss White
Flat Black
Amber
Chinese Red
Green



333 CXF



#### **PREMIUM FLUORESCENT**

- · Bright, reflective colors ensure instant visibility, for safety markings and warning signs
- Use on both interior and exterior surfaces

# Color 300-F103 Sunset Orange 300-F105 Titan Red



333 CXF



#### HIGH HEAT PAINT, **BLACK**

- · Ideal for BBQ and grills
- Withstands heat of up to 1200°F
- Helps prevent rust



# 300-HI0I



333 CXF



#### LACQUER PAINT, TRANSPARENT

# 300-L126





#### **PREMIUM** METALLIC PAINT, **ALUMINUM**

# 300-M103



333 CXF





#### **PREMIUM PRIMER**

- No sanding
- Improves adhesion, fills in imperfections
- Interior/exterior use
- Increases rust prevention

Color
Grey
Oxide Red
Black





#### RUBBERIZED UNDERCOAT

· Rubberized and asphalt coating for sealing, hiding repairs, rustproofing and sound deadening

333

CXF

- · Cannot be painted.
- Black, 439 g (15.5 oz)

# 400-20





#### **GRAVEL GUARD**

· Premium quality stone chip protector designed to protect rocker panels and other components

#	Color	Format
400-30	Black	20 oz
400-40C	Off White	15.75 oz
400-50C	Black	15.75 oz



333 CXF







#### ZINC MATETM

- Coating of >92% pure zinc actively fights rust and corrosion. Use as a touch-up for damaged galvanized coatings
- · Dries quickly
- 369 g





CRC



#### **RUBBERIZED SPRAY UNDERCOATING**

- A rubberized compound that provides a tough, flexible shield against moisture, salt and road debris
- · It dries quickly and is exceptionally resistant to abrasion
- 450 g

# 75034



218 CRC





#### **SEMI-PRO PAINTBRUSHES**

Straight bristles

#	Size (in)	Size (mm)
019010	1	25
019015	1-1/2	37
019020	2	50
019025	2-1/2	64
019030	3	75
019040	4	100



#### **ALL PURPOSE PAINTBRUSHES**

Straight bristles

#	Size (in)	Size (mm)
AP015210	I	25
AP015215	1-1/2	37
AP015220	2	50
AP015225	2-1/2	64
AP015230	3	75
	A	







518

#### **ECONO PAINTBRUSHES**

Straight bristles

#	Size (in)	Size (
010105	1/2	13
010110		25
010115	1-1/2	37
010120	2	50
010125	2-1/2	64
010130	3	75








#### **PARTS CLEANING BRUSHES**

#	Description	Size
12330	Tampico	#8





#### **HIGH DENSITY FOAM BRUSHES**

#	Size (in)	Size (mm)
050001	1	25
050002	2	50
050003	3	75



518





#### **GRAVEL GUARD® I**

- OEM Approved Rocker Panel Coating
- Paintable rocker coating, (aerosol or Schultz gun applied)
- For average or medium texture patterns
- Black



#	Format
BVGI	830 ml
SVGI	405 g
SVG124	550 g



#### **GRAVEL GUARD® III**

- · OEM Approved Rocker Panel Coating
- Paintable rocker coating, (aerosol or Schultz gun applied)
- For fine texture patterns
- Beige



609	#	Format
DSS	SVG3	550 g



#### **HI-BUILD WELD THRU™ PRIMER**

- Cold Galvanizing Spray. A very fast drying, anti-corrosive coating applied to metal surfaces prior to welding
- Reduces Mig weld "splatter" and can be applied to metal surfaces after welding
- · Gives corrosion protection before and after welding

#	Color	Format
SZC	Grey	410 g



### **SURE SEAL SEAM & JOINT SEALER**

- OEM Approved
- Paintable
- Non staining

#	Color	Format
CSC	Clear	300 ml
CSW	White	300 ml
CSB	Black	300 ml





#### **BRUSH ON SEAM SEALER**

- 100% rubberized for bare and primed metals
- · Permanently flexible & will not crack
- Holds a perfect "brush" mark to match that O.E.M. seam
- · Will adhere wet or dry and will not "sink" or "sag"
- Paintable in 20 minutes
- Light grey

PRGO

( 8 8.8	
#	Format
10025	350 g
	400

(i.e. garage door track)

**RUSTCHECK®** 

for exposed areas



609 DSS

Weather resistant corrosion protection

· Lubricates large metal moving parts



TBGQ		10000
	609	
	DSS	

# Format





#### **EZ LINER™**

- · Non flammable, non toxic, zero VOC.
- Anti-skid
- · Spray-on, roll-on or brush-on
- · Covers I large size truck bed

#	Format
BEZLG	l gal





#### HIPPO-LINER™ TRUCK BEDLINER

- New urethane based protective coating for applications to truck beds (replaces drop-in plastic liners), trailers, hoppers, boats, off-road vehicles, RVs and almost anything
- Protects surfaces against a wide range of extreme conditions
- Extends truck-box longevity

#	Format
	0.45 gal (1.7 L)





# GATOR GUARD® II EPOXY BEDLINER

- · Epoxy/urethane blended liquid
- Resistant to abrasions, gasoline, acids
- Excellent flexibility
- · Does not have any isocyanates
- Low VOC'S (volatile organic compounds)

#	Color	Format
BGG2	Black	0.45 gal (1.7 L)
BGG21	Black	1.8 gal (6.8 L)
BGG2W	White	0.45 gal (1.7 L)





#### **AEROSOL BEDLINER**

- Ultra chemical resistant aerosol bedliner
- Resistant to abrasions, gasoline, acids
- Used for touching up tears, scratches and chips in spray-in bedliners



609 DSS # Format
SEZL 467g



# FAST CURE PRIMERLESS URETHANE

- Fast setting autoglass urethane that provides excellent strength (MVSS 212 & 216)
- Can also be used as a high strength single component adhesive for re-applying moldings and ground effects

#	Format
CUSF	300 ml



609 DSS



# OEM APPROVED ASPHALT-BITUMEN BASE UNDERCOATING

- Non-paintable
- Excellent abrasion resistance, sound deadening and corrosion protection
- Aerosol or Schultz type can
- Black

#	Format
SUP	510 g
SUP20	405 g



609 DSS





#### **WEATHERSTRIP**

 High density self-sticking sealing tape stops drafts, rattles, etc. Ideal for trucks, cars, campers, tractors, air conditioning, computers, farm equipment, and industrial buildings



#	Size (in $x$ in $x$ ft)	#	Size (in $\times$ in $\times$ ft)
803	3/8 × 5/32 × 10	809	3/8 × 5/32 × 200
804	$3/8 \times 5/16 \times 10$	810	$3/8 \times 5/16 \times 100$
805	$3/8 \times 7/16 \times 10$	818	$3/4 \times 5/32 \times 100$
806	$3/4 \times 5/32 \times 10$	819	$3/4 \times 5/16 \times 50$
807	$3/4 \times 5/16 \times 10$	820	$3/4 \times 7/16 \times 50$
808	$3/4 \times 7/16 \times 10$	821	$1 \times 5/32 \times 100$



281 DRT

# KLEENGUARD® AUTOMOTIVE PAINTING COVERALL

- Outer layer treated to control lint and static and repellant to liquid splashes
- Passes NFPA 99 criteria for antistatic materials
- Meets ANSI/ISEA 101-1996 sizing standard

#	Size	
72213	Large	KleenGuard
72214	X-Large	AUTOMOTIVE PARITING
72215	XX-Large	PROGRAMME STREET
Kimberly-Clark	586	
	SCT	رنافا المالية
		N The Control of the

# KLEENGUARD® A40 LIQUID & PARTICLE PROTECTION APPAREL

- Zipper front; elastic wrists, ankles & hood. Better liquid and particulate barrier than TYVEK®
- · Passes NFPA 99 criteria for antistatic materials
- Low in lint
- Meets ANSI/ISEA 101-1996 sizing standard



586 SCT

#	Format
44322	Medium
44323	Large
44324	XLarge
44325	XXLarge
44326	XXXLarge

# PAINTABLE RUBBERIZED UNDERCOATING

- Fast drying product and an effective acoustic isolator
- Also protects underground pipes and containers
- 450 g

# 2785



201 KLF



# SPRAY UNDERCOAT & RUST RETARDER

- Ideal for touch-ups in wheel-wells and total body production. Dries in 20 minutes and an effective acoustic isolator
- 567 g

# 2783



201 KLF





#### MAXI-COAT™ HEAVY-DUTY RUSTPROOFING FILM

- Provides long-term protection for metal parts, equipment, and machinery
- · Forms a protective, waxy film which seals out moisture, air, acid, and other corrosive elements
- 12 oz



#### **EXTEND® RUST TREATMENT**

- One-step rust treatment that destroys old rust, prevents new rust
- Just brush or spray it on, and within minutes, rust disappears and is converted to a durable black protective coating
- · Use as a primer or finish coat
- · Specially formulated to be used with body filler and fiberglass
- I quart





#### **COLOR GUARD® TOUGH RUBBER COATING**

- · Inhibits rust and corrosion, seals, insulates, and won't crack or chip
- Acid and alkali resistant, lasts for years
- Use to 200°F
- · Dip, spray, or brush to apply
- 14.5 oz







#### **BLACK SATIN™ AUTOMOTIVE** TRIM COATING

- · Provides excellent adhesion to brass, galvanized steel and plastics
- 12 oz



# 3811





#### **BUMPER BLACK** PAINT

- · Renews and re-colors automotive plastics (flexible and rigid)
- Black, 12 oz



#### **TAL-STRIP® EXTRA** STRENGTH PAINT REMOVER

- · Removes enamel, lacquer, epoxy, urethane, varnish, shellac, decals, and gaskets from metal, wood, glass, concrete, stone, brick and ceramic tile
- Fast-acting, non-caustic
- · Clear, 15 oz



#### TAL-STRIP® IV URETHANE PARTS PAINT REMOVER

- Strip paints and coatings from urethane automotive parts without attacking and damaging the urethane substrate
- 17 oz









#### **RED SPOT** AND GLAZING PUTTY

- Stain-free tack-free premium polyester glazing and finishing putty
- · Best adhesion to steel galvanized steel aluminum E-Coat and SMC
- · Dries quickly with minimal shrinkage and superior flexibility
- 1 lb



### LONG STRAND FILLER

- · Polyester filler reinforced with fibreglass
- · Creates waterproof repairs that are twice the strength of ordinary body fillers
- · Use alone or in conjunction with fibreglass tape, cloth or mat
- · Previously sold as Marson® Stuff It®



#### **MAR GLASS® FIBERGLASS** REINFORCED POLYESTER FILLER

- · Creates waterproof repairs that are twice the strength of ordinary body fillers
- Use alone or in conjunction with fibreglass tape, cloth or mat

• 12 lb



#### **POLYESTER RESIN**

- · Quick curing and unbeatable flexibility
- I gallon



# 01403



MRS

#### **FIBERGLASS MATTING**

• 7 sq ft.



#### LARGE PAPER **MIXING BOARD**

- 13" × 10"
- White

# 20382 12 Ea. No. 20382 Disposable Paper Mixing Boards "Save There & Money" Banded on three sides to sturey heater beacci Provides a duration contaminate free purification and provided personal provided free purification of scales are purificated of scales are purificated of scales are purificated on the purification of th

> STORE IN A COOL DRY PLACE meters Manager Phone



**MRS** 



# KWIKEE™ IMPRINTED FIBER FLOOR MATS

- Protects carpets from soil and grease
- Put a fresh mat for delivery to show customers you care about their car
- 15" x 18", 250 per box

# 30203



940

MRS



# KWIKEE™ DISPOSABLE PLASTIC SEAT COVERS

- Special 2-ply Slip & Grip plastic, resist tears, tool punctures, splitting & stretching
- Covers high back bucket & bench style seats
- 125 per box





940

MRS

# KWIKEE™ DISPOSABLE PLASTIC WHEEL MASKERS

- These wheel maskers are a very inexpensive way to provide superior protection for wheels and tires during the painting process
- The rugged 2-ply plastic "clings" to the rim and tire
- 125 per box

# Size 30202 Small 30204 Large



940 MRS



#### **RUST DESTROYER PRIMER**

• 368 g

NLS PRODUCTS

. . . . .





 Quickly strips and removes decals, stickers, pinstripes and paint from bumpers, auto and truck bodies

203

**& PAINT STRIPPER** 

• 340 g

**DECAL** 

# 161DA



# 73013





#### TRUCK BED LINER

- Permanently bonds to the surface
- Textured and non-skid
- · Minimizes cargo slippage
- Will not warp or crack and is gasoline resistant

Plasti <b>Kote</b>	#	Size
	264	454 g aerosol
	265G	I gallon
387	265GK	I gallon Kit
PKP		-





#### **PREMIUM PRIMER**

- Non sanding
- Improves adhesion, fills in imperfections
- Increases rust prevention
- 340 g

#	Color
TI8	Gray
T19	Red Oxide
T25	Black
T38	White



387 PKP



#### **SANDABLE PRIMER**

- Provides strong adhesion and resists rust when applied to bare metal
- Works well under lacquer, enamel or acrylic top coats
- 340 g

#	Color
T234	Red Oxide
T235	Gray
T236	Black
T237	White



387 PKP



#### **ANTI-RUST ARMOR**

- Highest quality rust protection enamel for interior and exterior uses
- Dries to a rust resistant, scrubbable, stain-resistant finish
- Resistant to moisture, chemicals and abrasions





387 PKP

Color	Aerosol	Quart	Gallon
Gloss White	21900	21800Q	21800G
Satin White		21820	21820
Semi-Gloss White	21941		
Flat White	21921		
Gloss Almond	21935		
Gloss Safety Orange	21937	21837Q	21837G
Gloss Safety Yellow	21945	21845Q	21845G
Gloss Safety Red	21927	21827Q	21827G
Gloss Safety Blue	21959		
Gloss Dark Blue	21928		
Gloss Hunter Green	21944	21844Q	21844G
Gloss Brown			
Gloss Gray	21934	21834Q	21834G
Semi-Gloss Black	21942		
WI/Satin Black	21925		
Gloss Black	21924	21824Q	21824G
Flat Black	21926	21826Q	21826G
Heavy-Duty Aluminum	21940	21840Q	21840G
Gloss Clear Sealer	21955		
Red Oxide	21951		
Gray	21953		
White	21952		



#### **ENAMEL SPRAY**

- · For interior and exterior surfaces
- Use on wood or metal
- Fast drying
- 340 g

#	Color
2501	Gloss Black
2502	Flat Black
2504	Gloss White
2505	Clear
2506	Red
2508	Satin Black
2509	Yellow
2510	Gray
2512	Green
2516	Blue
2518 2519	Gray Sandable Primer Red Oxide Sandable Primer



# CHASSIS & GRILLE GUARD EPOXY PAINT

- Sprays-on evenly and dries to a factory-like finish
- · Resists cracking, chipping and peeling
- For use on prepared metals
- 340 g

#	Color
191	Gloss White
193	Gloss Black
194	Satin Black



387 PKP



PlastiKots

#### **ENGINE ENAMEL**

- Repeated exposure to engine heat up to 500°F will fuse engine enamel to the surface to increase bonding strength
- Fully resistant to oil and gasoline, will not weaken, crack, lift or peel
- Color choices are exact matches to original engine manufacturer standards
- 340 g

#	Color
198	Hot Rod Yellow
199	Hot Rod Green
200	Chevy Orange
201	Chevy Blue
202	Universal Gray
203	Universal Black
205	Old Ford Blue
206	Ford Red
207	Aluminum
208	Pontiac Blue
209	Universal Red
211	Hot Rod White
215	Low Gloss Black
216	New Ford Gray
221	GM Blue
223	Universal Gold
224	Ford Blue
225	Alpine Green
226	Chrysler Orange
227	Pontiac Blue Metallic
228	Gray Engine Primer
229	Clear
230	Flat Black
232	Chrysler Blue
233	Cummins Beige
	198 199 200 201 202 203 205 206 207 208 209 211 215 216 221 223 224 225 226 227 228 229 230 232




387 PKP



#### **REBUILDER'S CAST FINISH**

- $\bullet$  Fast-dry formulation resists oil, brake fluid and gasoline, and retains color up to  $300^{\circ}\text{F}$
- 340 g aerosol







#### **VINYL FINISH**

- · Adds fresh new Color, life and beauty to your vinyl surface
- Fuses to the original vinyl surface and forms a permanent bond
- · Won't crack, chip, chalk, peel or rub off
- Use it on car seats, dashboards and door panels
- 340 g aerosol



387 PKP

#	Color
405	Flat Black
408	Charcoal Gray
410	Gray
411	Black
412	White
413	Dark Blue
414	Dark Red
417	Brown
419	Buckskin
420	Flame Red



#### **TRACTOR & IMPLEMENT PAINT**

- Original OEM Colors
- Heavy-duty performance
- · Rust and fade resistant







387 PKP

Color	Gallon	Quart	Spray
IH Red	4431-01	4432-01	5339-01
MF Red	4431-02	4432-02	5339-02
AC Orange	4431-03	4432-03	5539-03
New Holland Red	4431-05	4432-05	
JD Yellow	4431-06	4432-06	5339-06
Trans Yellow	4431-07	4432-07	5339-07
New Equip Yellow	4431-08	4432-08	5339-08
New Holland Yellow	4431-09	4432-09	
JD Green	4431-10	4432-10	5339-10
Oliver Green	4431-11	4432-11	
Ford Blue	4431-12	4432-12	5339-12
Ford Gray	4431-13	4432-13	5339-13
Gloss White	4431-14	4432-14	
IH White	4431-15	4432-15	
Gloss Black	4431-16	4432-16	
Low Gloss Black	4431-19	4432-19	
Ford Red	4431-20	4432-20	
Kabota Orange	4431-24	4432-24	5339-24

#### **PREMIUM METALLIC PAINT**

- · Quickly and easily adds the "Midas Touch"
- · Provides a smooth and even coating
- For virtually all interior surfaces
- 340 g

#	Color
451	Silver
452	Gold



387 **PKP** 



#### TRUNK PAINT BASE COAT

- · Multi-Colored spatter finish renews and protects interior trunk surfaces
- 340 g

#	Color
500	Gray-White
501	Black-Gray
502	Dark Green-Aqua
503	Gray-Black-White



387 **PKP** 



#### TRUNK PAINT TOP COAT

· Provides a clear durable, moisture resistant sealant to be used over PlastiKote® trunk paint base coat

• 340 g







Plastikois

#### **FABRIC PAINT**

- · Exclusively formulated for re-Coloring carpet, velour and upholstery
- Penetrates natural and synthetic fabrics while preserving fabric flexibility and texture
- 340 g

#	Color
510	Ebony
512	Slate Gray

Plasti <b>Kote</b>	387
	PKP



#### **BUMPER PAINT**

· Gives a rich, satin finish that will revitalize faded, weathered rubber bumpers and side panel trim

• 312 g

#	Color
614	Gray
616	Black



#### **CHROME BUMPER PAINT**

• Produces a chrome-like finish perfect for chrome bumpers, grilles, hub caps and accessories

• 312 g

		PlastiKate or meets and
#	615	MANUAL CHECK
387		
PKP		DITINBUTE DANGER



#### WHEEL PAINT

- Provides a tough, long lasting finish that resists scratches and nicks, and will not tarnish, weather or rust
- 340 g

#	Color
618	Steel
620	Semi-Gloss Black
62 l 62 6	Silver Charcoal Gray Metallic





#### **SPOT FILLER & PRIMER**

- Covers nicks and scratches
- Successive applications build up quickly to the desired level
- 340 g

#	Color
464	Black
465	Red
466	Gray
467	Gray



# 468



#### **PAINT & PRIMER SEALER**

- Gray
- Excellent for sealing weathered vehicle paint prior to top coat application
- · Seals sandable primer and spot filler & primer products
- · Top coat with any PlastiKote® automotive paint
- 340 g







### PLASTIC PRIMER

- Clear
- Adheres to most automotive plastics
- For use on car interior pieces such as dashboards, consoles, etc.,
- · Also on flexible bumpers, trim and molding
- 340 g

340 g		
	<u>#</u>	469
PlastiKote	387	
	PKP	



### **ETCHING PRIMER**

- Gray
- · Chemically bonds to ferrous and non-ferrous metals
- Etches and primes in one coat
- · Provides a perfect surface for Spot Filler & Primer or top coat Colors
- 340 g

	#	470
PlastiKote	387	
	PKP	
F		



### ZINC RICH PRIMER

- Gray
- Cold galvanizing
- · Provides an excellent, NON-SANDABLE surface for any PlastiKote® automotive top coat
- 340 g

#	471



387 **PKP** 



### **HIGH HEAT PAINT**

- Black
- · Ideal for BBQ and grills
- Withstands heat of up to 1200°F
- Helps prevent rust
- 340 g

#	68004	valspar WHICH HEAL HICH HE
387		Distr.
PKP		POR NAME OF STREET
		THE DISTRICT



31 Pŀ

### **BRAKE CALIPER PAINT**

- 500°F coating that is chemical, chip and rust resistant
- 340 g

and the second	
Plastikote	387
	PKP



CP-250 Bright Yellow CP-251 Bright Red

CP-252 Bright Blue

CP-253 Hi-Gloss Black

CP-254 Hi-Gloss Silver



### **HI-TEMP PAINT**

- Formulated to resist intermittent temperatures up to I300°F
- · Ideal for use on headers, exhaust manifolds or any surface exposed to very high heat
- 312 g



#	Color
HPI3	Red
HPI4	Aluminum
HP15	Orange
HP16	Blue
HPII	Black
HP12	White
HP17	Cast Gray





### **PREMIUM FLUORESCENT PAINT**

- Bright, reflective Colors for safety markings and warning signs
- Use on both interior and exterior surfaces

• 312 g

U	
#	Color
FL6	Stop Light Red
FL7	Go Green
FL8	Pink
FL9	Caution Orange
FLIO	Yellow





387 PKP

### **LACQUER PAINT**

- Fast drying, deep-gloss coating with superb durability
- 340 g

#	Color
T3	Hot Rod Black
T33	Gloss White
T34	Gloss Black
T41	Dull Aluminum
T5	Clear
Plasti	Kote 387





### **CAMOUFLAGE PAINT**

- Use on almost anything you want to make "disappear" in the great outdoors
- 340 g

#	Color	
17035	Green	
17037	Brown	
17038	Black	
17039	Sand	







### PREMIUM ENAMEL

- Tough, hard wearing and resistant to scratches that will last for years
- · Very UV resistant, water resistant and will not fade or yellow
- 340 g

#	Color
ΤI	Gloss Black
TIO	Machinery Gray
TI2	Shamrock Green
T2	Flat Black
T23	Aluminum
T24	Flat White
T26	Slicker Yellow
T27	Antique White
T29	School Bus Yellow
T31	Bright Orange
T35	Astro Blue
T36	Chestnut Brown
T37	Federal Gray
T4	Gloss White
T43	Dark Cherry
T6	Swift Red
Т8	Satin Black
T45	Clear





<u>PlastiKote</u>	387
	PKP

### MARKING PAINT

- Sprays upside down for easy application
- · Can be used on all surfaces and is fast drying
- Non-clogging nozzle

#	Color
11740	Red-Orange
11741	Orange
11742	Red







### **PROFESSIONAL UNDERCOAT**

- Black protective coating
- Provides protection for wheel wells, gas tanks, frames and supports, weld joints, floor pans, doors and quarter panels
- 425 g

#	Color	
272	Rubberized	PlastiKote
273	Professional	CONTRACT POLICE SERVICES OFFICE
		UNDERCOAT HOUT DE PLANCE
		BUIT DE PLANCH
Plasti		

<b>P</b>	
Masti Kote	Plastikote



### **RUST NOT® RUST CONVERTER**

· Organically converts rust to an iron-hard, paintable surface

#	Format
623	8 oz
624	16 oz





387 PKP

### **ACETONE**

· Water miscible solvent and cleaner



075 **PFM** 

#	Format
PF602-5	946 ml
PF602-1	3.78 L
PF602	1891





### **SEAM SEALERS** AND ADHESIVES





075 PFM

#	Description	Color	Format
PF205			
DE0.0.4	Economical Seam Sealer	OffWhite	300 ml
PF206	Brushable Rubber Based Seam Sealer	OffWhite	946 ml
PF207	Rubber Based Economical Seam Sealer	Black	300 ml
PF209	Non-Sag Epoxy Seam Sealer	Taupe	200 ml Double Cartridge
PF211	Urethane Sealer / Adhesive	Grey	310 ml
PF212	Firm-N-Flex Premium Rubber Based Sealer	Clear	300 ml
PF213	Firm-N-Flex Premium Rubber Based Sealer	OffWhite	300 ml
PF214	Firm-N-Flex Premium Rubber Based Sealer	Black	300 ml
PF224	Urethane Sealer / Adhesive	Black	300 ml



## FAST CURE URETHANE WINDSHIELD ADHESIVE



#	<b>Description</b> Fast Cure	<b>Color</b> Black	••••••••••••
PF225		Diack	310 1111
PF230	Pinchweld & Glass Bond Primer	Clear	30 ml
PF300	Dum Dum Strip Caulk	Black	4.7 mm × 305 mm (3/16" × 12") 908 g
PF301	Dum Dum Strip Caulk	White	4.7 mm × 305 mm (3/16" × 12") 908 g
PF410	Butyl Tape		Round 8 mm × 4.5 m (5/16" × 15")
PF411	Butyl Tape		Square 8 mm × 4.5 m (5/16" × 15")
PF412	Butyl Tape		Round 9 mm × 4.5 m (3/8" × 15")
PF413	Butyl Tape		Square 9 mm x 4.5 m (3/8" x 15")

### **WEATHERSTRIP ADHESIVE**

#	Description	Format
PF505	Sprayable Adhesive	333 g aeroso
PF528	Heavy Duty Trim Adhesive	446 g







### **BODY FILLERS**



#	Description	Format
PF151-1	Gold One Step Body Filler	3.0 L
	(Fill & Finish)	
PF151-2	Gold One Step Body Filler	1.5 L
	(Fill & Finish)	
PF155	Hi Performance	750 ml
	Lightweight Body Filler	
PF155-1	Hi Performance	3.0 L
	Lightweight Body Filler	
PF160	Aluminum Filled	750 ml
	Repair Compound	
PF164	Short Strand	750 ml
	Reinforced Filler	
PF164-1	Short Strand	3.0 L
	Reinforced Filler	



### PREMIUM/FLOWABLE/FLEXIBLE PUTTIES



#	Description	Format
PF158	Premium Finishing Putty	500 ml
PF158-2	Premium Finishing Putty	1.5 L
PF167	Flowable Blending and Finishing Putty	710 ml
PF177	Glazing & Spot Putty	150 ml




### FLOWABLE BLENDING & FINISHING PUTTY

#	Description	Format
PF319	Flowable Blending & Finishing Putty	150 ml
PF325	Premium Finishing Putty	281 ml





### FIBREGLASS REPAIR KITS





### **FIBREGLASS RESIN**

#	Description	Format
PF 175	Fibreglass Polyester Resin	946 ml
Pf 175-1	Fibreglass Polyester Resin	3.78 L



075 PFM





# PF636

PF637

Filler

Filler

### **UNIVERSAL HARDENER**

# Format
PF597C 946 ml
PF598C 473 ml





## HARDENERS FOR FILLERS, PUTTIES AND RESINS

#	Description	Color	Format
PF140	Cream Hardener	Blue	28 g
PFI4I	Cream Hardener	Blue	78 g
PF145	Liquid Hardener	Clear	14 ml
PF146	Liquid Hardener	Clear	44 ml



Description Color
High Build Primer/ Buff

High Build Primer/ Light Grey 425 g

Format 425 g

aerosol

aerosol

### **2K URETHANE PRIMER SURFACER-BUFF**

#	Description	Format
PF490-1	DTM 2K Urethane	3.78 L
	HB Primer	
PF491	DTM 2K Urethane	946 ml
PF659C	Primer Catalyst	227
PF659C	2K Urethane Primer Surfacer Catalyst	236 ml
PF656C	2K Urethane Primer	3.78 L
110500	Surfacer, grey	3.70 L
PF658C	2K Urethane Primer	946 ml
	Surfacer, grey	
PF674C	Acrylic Primer Surfacer,	3.78 L
PF675C	grey	046
PF6/3C	Acrylic Primer Surfacer, grey	946 ml
PF661C	2K Epoxy Primer/Sealer,	3.78 L
	grey	
PF660C	2K Epoxy Primer/Sealer	3.78 L
	Catalyst	
PF663C	2K Epoxy Primer/Sealer	
PF662C	Catalyst 2K Epoxy Primer/Sealer,	2 70 1
FF002C	black	J./0 L
PF664C	2K Epoxy Primer/Sealer,	946 ml
	grey	
PF654C	IK Self Etching Primer,	340 g
	grey	aerosol

PF657	Filler		Olive Green	aerosol
100	21/100; 2K Urothano Suracar - B	PORM.	2) Vo.0; 2) Vo.0; 2) Virgitane Prinver Surfacer - Buff Lappin dicthane 1) Pagent 2N - Virgin	
influence care care care care care care care ca	Primer Can Can		EXTREME DANS PANGER EXTR	ER ME PF 650C
DA TORRESTOR	Sanfarer .	POPULATION OF THE POPULATION O		
PRO 6	EXTREME DANGER	DAIS PI S		

PFM

## WAX AND GREASE REMOVER

#	Description	Format		mo(t)
PF605-1	General Purpose Adhesive Cleaner	3.78 L	PRO ( FORM'	Pomover Science/I
PF621	Wax & Grease Remover	946 ml	300	
PF511	All Purpose Surface Cleaner	503 g aerosol		(9)
PF603-1	Final Wipe Solvent / Cleaner	3.78 L	075	DANI
PF620	Final Wipe Solvent	946 ml	PFM	PF 621



### **URETHANE GRADE REDUCER**

#	Description	Format	Speed	Iemperature Range
PF684-1C	Urethane Grade Reducer	3.78 L	Fast	16 °C – 21 °C (60 °F – 70 °F)
PF683-1C	Urethane Grade Reducer	3.78 L	Medium	18 °C – 27 °C (65 °F – 80 °F)



075 PFM

### PRO GUARD RUBBERIZED **GRAVLGUARD**

#	Description	Color	Format
PF565	European Texture Rubberized Gravelguard	Blanc cassé	446 g aerosol
PF566	European Texture Rubberized Gravelguard	Grey	446 g aerosol
PF560	European Texture Rubberized Gravelguard	Black	446 g aerosol
PF532	Pro Guard Rubberized Gravelguard	Black	560 g aerosol
PF500	Non-Paintable Rubberized Undercoat	Black	560 g aerosol
PF561	Non-Paintable Rubberized Undercoat	Black	439 g aerosol



075 PFM



### **RUSTPROOFING**

#	Description	Format	Color
	Wax Based Permanent Rustproofing		



PRO FORM

075 PFM



### **RUST REMOVER**

#	Description	Format
PF535	Sprayable	531 g
	Paint Stripper	aerosol

075

PFM



DescriptionFormatWaterborne P200 g aerosol PF588 Formulation PF589 Universal 215 g aerosol

**AEROSOL CUSTOM FILLING SYSTEM** 



PRO FORM' 075 PFM

Solvent



## SPRING STEEL BODY FILLER APPLICATOR SETS

# # Description Pieces 9025 6" (15.2 cm) 2 9024 2.5 to 10 cm 4



## PLASTIC BODY FILLER APPLICATORS

# Qty/Box 9027F 3 9027FB 50





• 3", 4", 5" (7.5 cm, 10 cm, 12.5 cm)



068 PTK

# 9028



### **3-PIECE BRUSH SET**

• Includes one brass, stainless steel and nylon brush



068 PTK

# 6901



## PRO-TACK® GOLD TACK CLOTHS

- Extra-sticky for very dusty jobs
- 24 per box





068 PTK

# PRO-TACK® BLUE TACK CLOTHS

- For light dusting jobs
- 24 per box



### **PLASTIC RAZOR BLADES**

• 100 per box





068 PTK

### **FIBERGLASS MAT**

• Strong, yet flexible, and easy to shape

PTK

- · Bonds to most rigid materials
- Resists water and acid

# Description (sq.ft.)
58045 32 (2.9 m²)
58075 8 (0.7 m²)



РТК



### **GUN WASH**

- · For cleaning spray guns and lacquer painting equip-
- · Less flammable than Acetone
- 18.9 L



### **FIBERGLASS RESIN**

- · Thicker viscosity for less running and sagging
- Fast curing
- Tack free
- Waterproof and impact resistant
- Liquid hardener included





424 **REC** 



944 usc

### PAINTER'S PAIL™ MIXING CUPS

- · Measure and mix primers, clears, single stage, basecoat and any refinishing product in these sturdy, solvent resistant clear plastic mixing cups
- U.S. & Metric liquid measurements
- Includes most common mix ratios
- Markings visible from the inside or outside
- Lids available for all pails

#	Description	Case
36175	Lid for I-quart pail	3
36176	2.5-quart Painter's Pail™	9
36177	Lid for 2.5-quart pail	4
36178	5-quart Painter's Pail™	15
36179	Lid for 5-quart pail	6

# e (lbs) 944 usc

### **SLIP-N-GRIP® PROTECTIVE SEAT COVERS**

944

USC

· Double-layer design, individually folded

125 per box



# 58065

FIBERGLASS CLOTH

· Flexible, ideal for contouring

Resists water and aci

Bonds to most rigid materials



944 USC



**50** 



### PROPANE CYLINDER

- · Perfect for use with portable propane camping appliances
- 16.4 oz recyclable, non-refillable cylinder





854 **BZM** 



### **DISPOSABLE OXYGEN CYLINDER**

- Use with propylene gas for hottest brazing performance and light cutting/welding
- 1.4 oz.



# 304180 (TTU688)



854 **BZM** 



### **BUTANE CYLINDER**

- · Ideal for light or detailed soldering
- For use with BernzOmatic Micro Torches
- Flame temperature in air = 3,200 degrees (F)
- 5.5 oz



329853 # (BF55)



854 **BZM** 



### PROPANE CYLINDER

- · Use with torches and most portable appliances requiring propane
- |4,|-07.

304184 (TTU686)



BERNZÔMATIC

854 **BZM** 

### MAP-PRO™ GAS **CYLINDER**

- Burns hotter than propane!
- · Use only with torches and appliances specifying "for use with propylene"
- 14 oz

332478 (TTU687)





854 BZM

### SPARK LIGHTER

· Creates a spark to light most propane and propylene gas fueled torches quickly and easily

Replacement Flints # Description TX405 Single Flint TX406 (Pack of 5) Lighter



854 **BZM** 



### **METAL WORK SOLDER**

- Silver bearing lead-free acid core solder for increased joint strength
- · Acid core based flux No flux necessary



854 BZM



# Size
327796 3oz
(SAC300)
327797 8oz
(SAC800)

### **PLUMBER'S SOLDER**

- Solid wire
- Lead-free: NSF 61 certified safe for potable water systems
- Meets ATSM standards B32
- Silver bearing solder for increased joint strength



854 BZM



#	Size
327790	3 oz
(SSW300)	
327791	8 oz
(SSW800)	
327792	16 oz
(SSW1600)	

## LEADED SOLID WIRE SOLDER

- 0.062" diameter
- 420°F melt temperature
- Not for plumbing







854 BZM

### **ELECTRICAL SOLDER**

- Premium silver bearing lead-free rosin core solder for increased joint strength
- Rosin Core Based Flux No Flux Necessary

#	Size
327788	0.75
(SRC050)	
327793	3 oz
(SRC300)	
327794	8 oz
(SRC800)	





## WATER SOLUBLE PLUMBING FLUX

- · For general use
- I oz

Size
l oz



854 BZM



## PETROLEUM-BASED PLUMBING FLUX

- · For general use
- I oz

# 327802 (PF200)



854 BZM





### **INDUSTRIAL GUN AND KIT**

- Kit contains D650 soldering gun with one soldering tip and a coil of lead-free solder
- 300 watts in high trigger (1st) position and 200 watts in low trigger (2nd) position
- 2-wire or grounded cord
- UL and cUL listed
- 7-year limited warranty





### PROFESSIONAL GUN AND KIT

- Kit contains D550 soldering gun with I soldering tip, I smoothing tip, I cutting tip, flux brush, soldering aid tool and a coil of lead free solder
- Dual-heat gun produces 260 or 200 watts
- UL and cUL listed
- 7-year limited warranty





### UNIVERSAL GUN AND KIT

- Kit contains 8200 dual heat soldering gun, I soldering tip, I smoothing tip, I cutting tip, flux brush, soldering aid tool and a coil of lead free solder
- Dual-heat gun produces 140 or 100 watts
- UL and cUL listed
- 7-year limited warranty





## BATTERY POWERED SOLDERING IRON KIT

- Over 120 intermittent solder joints with fresh batteries
- Perfect for field service repair on small parts and components
- Includes iron, tip, 3 AA batteries, lead free solder, and tip wrench



## MAGNA-LITE BUTANE TABLE TOP TORCH

- · Adjustable flame height
- Up to 60 minutes continuous use controls flame temperature up to 2,400° F
- Refillable with Weller® WBI or WB2 filtered butane








## PORTASOL® SUPER-PRO SELF-IGNITING KIT AND TOOL

- Kit contains PSI100 iron, sponge, stand and extra tips packed in a plastic case
- Features "Auto Switch" safety shut-off, iron plated tips, and built-in butane filter
- Adjustable temperature up to 1,076°F
- Refills with butane fuel Weller® cat no.WB1 or WB2







### PREMIUM BUTANE FUEL

- Compatible with Weller® Portasol®, Pyropen®, and Magna-Lite tools
- 2.1 oz







### REPLACEMENT TIPS FOR SOLDERING GUNS

· Copper tips, compatible with Weller® soldering guns

#	Description	Description	Description
6160	Tip Only	8200(PK)/D550(PK)	Smoothing
7135W	Tip Only – 2 per Bag	8200(PK)	Standard
7250W	Tip Only – 2 per Bag	D550(PK)	Standard
7250N	Tip with Hex Nut	D550(PK)	Standard



128 COS



## TIPS FOR WELLER®/PORTASOL® CORDLESS BUTANE SOLDERING IRONS

• Buses de cuivre compatible avec les pistolets à souder Weller<sup>MD</sup>2, loz

#	Use with	Туре	Tip Size (in)	Tip Si	ze (mm
PPTI	P2C/P2KC	Single Flat	0.031	0.80	-
PPT6	P2C/P2KC	Double Flat	0.094	2.40	
PSH	PSII00	Single Flat	0.031	1.00	-
PSI10	PSII00	Hot Knife	_	_	and the last of



128 COS



### **GAS WELDING RODS**

- · Flux coated
- Low furning
- Fuses well with cast iron, malleable iron, galvanized iron, steel, brass and copper
- 65,000 PSI tensile strength



372
FIR

#	Size (in)	Weight (lb)
1440-0431		
1440-0429	$3/32 \times 36$	5
1440-0430	$1/8 \times 36$	5

### **BRAZING & SILVERFLOW RODS**

#	Description	Pack
1440-0026	12 pieces, 3/32" x	0.5 lb tube
	18" round rods	(

1440-0434 1/8" x 18" | I lb tube







### HARDFACING ELECTRODES

- High impact and abrasion resistance
- High deposition rate prolongs surface life of new and worn parts
- Ideal for repairing all types of agriculture, construction equipment, auger, buckets, concrete mixers, etc.





372	
FIR	

#	Description	Pack
1440-0080		I lb tube
1440-0081	1/8" #35	5 lb box

# ENIFECL NICKEL 55 CAST IRON ELECTRODES (MACHINABLE)

- Repair cast iron, heavy cast iron sections
- Produce strong, sound welds at low amps
- Repairs cylinder blocks, exhaust manifold, and machine bases.
- Current: AC/DC DC+ recommended
- 1/8" × 1 lb





### **308 STAINLESS STEEL ELECTRODES**

#	Size (in)	Pack
1440-0165	3/32 × 14	l lb
1440-0155	$1/8 \times 14$	l lb
1440-0156	$1/8 \times 14$	5 lb



372 FIR





### **PREMIUM AWS ARC WELDING RODS**

Description	Rod (in)	l lb	5 lb	10 lb	50 lb
Class E-6011 Mild Steel	3/32	1440-0115	1440-0116	1440-0117	1440-0118
Class E-6011 Mild Steel	1/8	1440-0105	1440-0106	1440-0107	1440-0108
Class E-6011 Mild Steel	5/32	1440-0095	1440-0096	1440-0097	1440-0098
Class E-6013 Mild Steel	3/32	1440-0145	1440-0146	1440-0147	1440-0148
Class E-6013 Mild Steel	1/8	1440-0134	1440-0135	1440-0136	1440-0137
Class E-6013 Mild Steel	5/32	1440-0124	1440-0125	1440-0126	1440-0127
Class E-7014 Iron Powder	3/32	1440-0205	1440-0206	1440-0207	1440-0208
Class E-7014 Iron Powder	1/8	1440-0200	1440-0201	1440-0202	1440-0203
Class E-7014 Iron Powder	5/32	1440-0150	1440-0151	1440-0152	1440-0153
Class E-7018 Low Hydr.	3/32	1440-0195	1440-0196	1440-0197	1440-0198
Class E-7018 Low Hydr.	1/8	1140-0185	1140-0186	1140-0188	1440-0187
Class E-7018 Low Hydr.	5/32	1440-0180	1440-0181	1440-0182	1440-0183



372 FIR





### **ER70S-6 SOLID MIG WIRE**

#	Wire Size (in)	2 lb	I I lb	33 lb
ER70S-6	.023	1440-0210	1440-0211	1440-0212
ER70S-6	.030	1440-0215	1440-0216	1440-0217
ER70S-6	.035	1440-0220	1440-0221	1440-0222
ER70S-6	.045	N/A	N/A	1440-0447



372 FIR



### **E71T-GS FLUXED CORE WIRE**

Wire Size (in)	2 lb	I I lb	25 lb	10 lb
.030	1440-0230	1440-0232	N/A	1440-0231
.035	1440-0235	1440-0236	1440-0237	N/A



372 FIR



## ER-5356 MIG ALUMINUM SOLID WIRE

Wire Size (in)
.030
.035
.035



372 FIR





### **LEAD FREE SOLDER**

- Used for non-electrical applications
- Applications include Plumbing and Refrigeration systems
- 95% Tin, 5% Antimony

Pirepower

#	Description	Weight
	Lead Free, 95/5	1/8"×1 lb
1423-1116	Lead Free, 95/5	$1/8" \times .5 lb$



### SOLDERING FLUX AND PASTE

- Soft Soldering/Tinning Flux that is active between 200°F and 600°F
- Very effective on copper and repairing automotive radiators

#	Description
	2 oz Soldering Flux
1423-1101	2 oz Soldering Paste







### **ACID AND ROSIN FLUX**

372

FIR

#	Description	Weight		
1423-1102	Acid Flux Core, Comm.	1/8"×1 lb		A PARTIE
1423-1109	Acid Flux Core, 30/70	$1/8" \times 1/2 \text{ lb}$		3751
1423-1108	Acid Flux Core, 40/60	$1/8" \times 1/4 \text{ lb}$	Pirepower	TOWN CORE M
1423-1114	Rosin Flux Core, 40/60	1/8"×1 lb	100	
1423-1113	Rosin Flux Core, 30/70	$3/32" \times 1/2 lb$		
1423-1110	Rosin Flux Core, 40/60	$1/16" \times 1/4 lb$	372	
1423-1112	Rosin Flux Core, 40/60	$3/32" \times 1/4 \text{ lb}$	FIR	

## ALUMINUM BRAZING FLUX POWDER

# 1423-1118





### **ANTI-SPATTER SPRAY**

- Prevents spatter adhesion on surface and reduces clean-up time
- Non-flammable contains no silicones
- 16 oz

# 1440-0296





### **CUTTING TIPS**

- Victor style Firepower 350 style cutting attachment
- Tellurium copper construction
- Flame tested

Size (in)	#	Size (in)
3/8 - 1/2	0387-0147	
3/4	0387-0146	3/4
	0381-0184	3/4
3/8 - 1/2		
	(in) 3/8 - 1/2 3/4	(in) # 3/8 - 1/2 0387-0147 3/4 0387-0146 1 0381-0184





### **WELDING HOSE**

- Meets or exceeds RMA and CGA requirements
- Warning! "Grade R" welding Hose is recommended for use with Acetylene Gas only

ior use with	Acetylene Gas only	
#	Wire Size	
1412-0012	3/16" x 12.5 ft. (Dual)	R
1412-0020	$3/16" \times 25 \text{ ft. R}$	
1412-0021	$I/4" \times 25$ ft. R	Firepower
1412-0022	$I/4" \times 50$ ft. R	36.



### **FLINT LIGHTERS**

#	Description	Replacement Flints
1423-0026	Single Flint Lighter	1423-0032
1423-0050		1423-0052
Pirepower	372	
	FIR	

### **PROPANE TANK**

• 14.1 oz, 8.65 CF, CGA 600

# 0387-0436





### **TIP CLEANERS**

- Set of 13 cleaners with file
- Sizes #6 through #26 for cleaning Drill Size 77-49



### CHIPPING HAMMER

# 1423-0086



372 FIR



### **BRUSHES**

RKO2HE2			
#	Description	No of Rows	Trim Length (in)
1423-0087	Long Curved Carbon	3 × 19	1.1875
1423-0082	Long Curved Stainless	3 × 19	1.1875
1423-0083	Shoe handle Carbon	4 × 16	1.1875
1423-0081	Toothbrush Stainless	$3 \times 7$	1/2
1423-0093	1/2" Paintbrush	N/A	3/4
	MANAGEMENT OF THE PROPERTY OF THE PARTY OF T	Misim	
Management	11111	Millian	



372 FIR



## WELDER'S SAFETY AND CHEMICAL SPLASH GOGGLES

- 50mm, shade No. 5
- Meet/exceed ANSI Z87.1 and various International Standards



### WELDER'S LIFT FRONT GOGGLES

- · Shade No. 5
- Meet/exceed ANSI Z87.1 and various International Standards



### **WELDER'S SAFETY GOGGLES**

FIR

- Shade No. 5
- Hooded vents prevent fogging and offers excellent ventilation
- Meet/exceed ANSI Z87.1 and various International Standards



### **GRINDING SHIELD**

- Ratcheting
- Meets/exceeds ANSI Z87.1 and various International Standards



### **CLEAR SAFETY GOGGLES**

• Meet/exceed ANSI Z87.1 and various International Standards





### **SOAPSTONE WITH HOLDER**

Description
Flat Soapstone, 6 pcs./pk
Round Soapstone, 6 pcs./pk
Flat Soapstone Holder
Round Soapstone Holder





### 12-PIECE TIP DRILL CLEANER KIT

 Contains most commonly used 12 drills (#57-74) in assorted sizes





### **WELDER'S GLOVES**

• Wing thumb, I 4" flared gauntlet cuff and self hem

• Size: L

#	Description
1423-0051	Welder's Gloves
1423-4133	Premium Welder's Glove







372 FIR



### **ELECTRICAL TAPE**

- 3/4" × 66', 7 mil
- Cold resistant

DOCAP

• Temperature rating -7°C to + 80°C

# 554-500





### **COLD WEATHER** TAPE

- 3/4" x 66', 8 mil
- Cold resistant and flame retardant
- Temperature rating -19°C to + 90°C

# 554-100B



080 DCP



### **MASKING REFILL ROLL**

· Designed to prevent paint seepage

080

DCP

- Excellent adhesion, release and cornering properties (good release from rubber and after bake cycle)
- 18 cm × 20 m (7" × 65')

#	Description
	Refill roll
48218	Dispenser/Refill roll



069 FBS

### **PROMASK TAPE & PAPER/REFILL**

• 12" × 24 yards (30 cm × 25 m)







### TRIM EDGE TAPE

- Elongation: 5%
- Temperature resistance: Ih/I50°C (302°F)
- Excellent waterborne resistance

# K-TM21





069 FBS

### **PROBAND F-178 FINE LINE TAPE**

· 60-yard (55-meter) roll

#	Width (in)	Width (mm)
48405	1/16	1.6
48410	1/8	3
48420	1/4	6
48430	1/2	12







### YELLOW MASKING TAPE

- Offers solvent and moisture resistance that minimizes bleed through; also delivers a controlled unwind that makes tape easier to handle
- · Semi-smooth backing is thin and conformable
- Produces sharp, clean, quality paint jobs

#	Size (mm x m)
06652	18 × 55
06654	$36 \times 55$
06656	$48 \times 88$





130 MMM

### SCOTCH® MASKING TAPE NO 2308, NATURAL

#	Description
06545	18 mm × 55 m 5.5 mil
06547	36 mm x 55 m 5.5 mil
06548	48 mm x 55 m 5.5 mil



130 MMM



### TRIM MASKING TAPE

- Designed to lift moldings allowing complete paint coverage under it while protecting the front from paint overspray
- Eliminates sharp paint edges, speeds vehicle painting
- · 10 mm width





130 MMM

### SCOTCH® PERFORMANCE MASKING TAPE NO 233+, GREEN

- Highly conformable, provides the best adhesive transfer resistance, hugs curves, contours and provides outstanding paint lines
- Goes on quickly and easily, sticks at a touch and stays put

#	Description		100
26334	18 mm x 55 m	(3/4")	· · ·
26336	24 mm x 55 m		
26338	36 mm x 55 m		
26340	48 mm x 55 m		13
26344	1/4" (6.5 mm)		
28/		(B)	1
	130	Maria	
	MMM		

### HIGHLAND™ MASKING TAPE NO 2727, NATURAL

#	Description
06541	18 mm × 55 m 5.5 mil
06542	$36 \text{ mm} \times 55 \text{ m} 5.5 \text{ mil}$
06543	48 mm × 55 m 5.5 mil



130 MMM

# AUTOMOTIVE ACRYLIC PLUS ATTACHMENT TAPE, BLACK

- Good peel and shear adhesion to most automotive surfaces, with good internal strength and high conformability
- OEM approved
- 60 mil, 1/2" × 60' (12.7 mm × 18.3 m)





130 MMM





## AUTOMOTIVE ACRYLIC PLUS ATTACHMENT TAPE

- OEM approved and are stronger, higher performing, high stress handling products than other automotive attachment tapes
- 1.2 mm (0.045") thick

#	Dimensions (in x ft)
06382	$1/2 \times 60 (12.7 \text{mm} \times 18.3 \text{m})$
06383	$7/8 \times 60 (22.2 \text{mm} \times 18.3 \text{m})$
06384	$1/2 \times 15 (12.7 \text{mm} \times 4.6 \text{m})$
06386	$1/4 \times 60 (6.3 \text{mm} \times 18.3 \text{m})$





### **VINYL TAPE 471+, BLUE**

- · Good solvent resistance
- Conformability and dead stretch properties are ideal for many curved, convex, or irregular surfaces
- Clean removal from many surfaces
- Compatible with waterborne paints

3M	130		
	ммм		

#	Size (in)
06404	1/8 (3.2mm)
06405	1/4 (6.3mm)
06408	1/2 (12.7mm)
06409	3/4 (19 Imm)



### **SCOTCH® ELECTRICAL MOISTURE SEALANT ROLL**

- Self-fusing, rubber-based thin insulating mastic compounds laminated to a flexible, with an all-weather grade PVC backing
- $2-1/2" \times 10' (6.3 \text{ mm} \times 3\text{m})$
- 45 mil



# 06147



### **DUCT TAPE NO 3939, SILVER**

# 06975



130 MMM



### SCOTCH® VINYL ELECTRICAL TAPE

- · UL listed and CSA certified
- 105°C (220°F) down to -18°C (0°F)

#	Description	Thickness	Size
06132	Super 33+	7 mil	3/4" × 66' (19 mm × 20.1 m)
06143	Super 88 Premium	8.5 mil	$3/4'' \times 66' (19 \text{ mm} \times 20.1 \text{ m})$



130 MMM





### **OVERSPRAY PROTECTIVE SHEETING**

- Paintable, high-density, tear-resistant, translucent film designed for critical edge masking as well as protection from paint overspray
- · Tear-resistant, clear and durable
- 0.4 mil



130 MMM



### **DIRT TRAP MATERIAL**

- Specially engineered adhesive-backed material designed to protect paint booth walls and floors, trap dust and overspray and brighten work areas
- Can also be used to help protect other areas in the shop such as: table tops, paint scales, paint mixing rooms walls and floors, prep bays areas, etc
- 28" × 300' (71.1 cm × 91.4 m)

# 36852



130 MMM

### BLACK LIQUID ELECTRICAL TAPE


- Seals electrical connections
- Applies as liquid, then cures to a flexible, inyl polymer
- Dielectric stength: 1,700 volts per mil thickness
- 4 oz

# 85121





### **MUFFLER TAPE**





### **DOUBLE SIDED ACRYLIC FOAM TAPE**

#	Description Tape Grey/Red liner	Size mm x m	Size in x ft	Thickness mm	Thickness in
PF950	2 Sided Acrylic Foam	$12 \times 18$	$1/2 \times 60$	0.8	0.045
PF955	2 Sided Acrylic Foam	$12 \times 4.5$	1/2 ×15	0.8	0.045
PF951	2 Sided Acrylic Foam	16 × 18	$5/8 \times 60$	0.8	0.045
PF952	2 Sided Acrylic Foam	$22 \times 18$	$7/8 \times 60$	0.8	0.045
PF956	2 Sided Acrylic Foam	$22 \times 4.5$	$7/8 \times 15$	0.8	0.045
PF949	2 Sided Acrylic Foam	6 × 18	$1/4 \times 60$	0.8	0.045

#	Description Tape	Size mm x m	Size in x ft	Thickness mm	Thickness in
PF940	2 Sided grey/red liner	12×18	1/2 × 60	0.8	0.045
PF941	2 Sided grey/green liner	19 × 18	$3/4 \times 60$	0.8	0.045

#	Description Tape Grey/Red liner	Size mm x m		Thickness mm	Thickness in
PF954	Premium 2 Sided Acrylic Foam	6 × 4.5	.236 × 15	0.8	1/32
PF957	Premium 2 Sided Acrylic Foam	$12 \times 18$	$1/2 \times 60$	1.14	0.045
PF958	Premium 2 Sided Acrylic Foam	$22 \times 18$	$7/8 \times 60$	1.14	0.045

		Size	Size	Thickness	Thickness
#	Description Tape Grey/Red liner	mm x m	in x ft	mm	in
PF953	Name Plate Repair	6 × 4.5	.236 × 15	0.8	1/32

		Size	Size	Thickness	Thickness
#	Description Tape Black	mm x m	in x ft	mm	in
PF939	Pickup Truck/Camper Cap	38 × 9	$1-1/2 \times 30$	5	3/16
PF938	Pickup Truck/Camper Cap	51 x 9	$2 \times 30$	5	3/16





075 PFM



## MOLDING TAPE ADHESION PROMOTER

# **Size**PF946C 220 ml





075 PFM

### **LIQUID MASK**

- · Water-based clear liquid mask
- Protects against paint overspray
- Excellent for booth coating
- · Will dissolve easily when washed with cold water
- Use on door jambs, engine compartments, wheel wells, grilles, etc.
- Transparent

# Slze
PF450-1 3.78 L
PF450-15 18.9 L
PF450-5 58 L
PF450-55 205 L



075 PFM



### **KRAFT MASKING PAPER**

- Economical vehicle masking paper
- · Excellent for automotive, aviation, marine and industrial use

Size (in)
6 - 225M/RL
12 - 225M/RL
18 - 225M/RL
24 - 225M/RL
36 - 225M/RL





138 BNR

### **POLYCOAT MASKING PAPER**

- Blue in color to allow better natural light reflection in your paint booth
- Prevents bleed-through
- · Treated on the exterior surface to allow a cleaner dust-free surface prior to painting
- Resistant to automotive paint strippers

Size (in)
12 - 225M/RL
18 - 225M/RL
24 - 225M/RL
36 - 225M/RL





## ORIGINAL COLD WELD ADHESIVE

- Adhesive, laminate, plug, filler, sealant, and electrical insulator
- Withstands up to 600° F
- Adheres to metal, copper, steel, wood, concrete, marble, and fibreglass
- Compressive strength 10,733 PSI, flexural strength 7,320 PSI
- 2 oz





## GRAY INDUSTRO WELD TWIN TUBES EPOXY

- Adhesive, laminate, plug, filler, sealant and electrical insulator
- · Drill, tap, sand, and paint it
- Withstands 600° F
- · Will adhere to all surfaces
- Two 5 oz tubes

# 8280 247 JBW



### **KWIKWELD EPOXY GLUE**

- 4 minutes to set and 4-6 hours to cure
- For Fix-it-Fast Repairs
- Perfect for repairs at home, on the farm or in the shop
- Non-toxic and temperature resistant up to 300°F
- · I oz steel & I oz hardener





### **MARINEWELD GLUE**

 Ideal for maintaining and repairing a wide variety of boating and marine products

# 8272

- · Cures as strong as steel
- · Water- and weather-proof
- Impervious to saltwater, chemicals, oil, acids, and other corrosive materials
- 2 oz

247

**JBW** 



### WATERWELD EPOXY STICK

- Designed for repairs in moist applications and underwater applications
- Adheres to fiberglass, PVC plastic, copper, iron and aluminum
- Can be drilled, sanded, filed, tapped, machined and painted
- · Cures in 60 minutes
- 2 oz





### STEELSTIK ADHESIVE

- Adhesive, laminate, plug, filler, sealant, and electrical insulator
- Will cure on a wet surface including gasoline.
- Will adhere to all surfaces
- Compressive strength 14,000 PSI
- 2 oz





### **SEMI-RIGID EPOXY ADHESIVE FILLER**

- A two-component semi rigid modified epoxy designed as an "ALL PURPOSE" plastic repair material
- Works on all plastics including the "tough to bond" plastics (TPUR, PUR, RIM, PP,TPO,TPE)
- Use over Urethane Repair material (XSMAP, XSM2002)
- Easy sanding and feather edging characteristics
- May also be used as a multipurpose adhesive.



609 DSS







### **MUFFLER CEMENT**

- · Adheres to exhaust parts to repair holed muffler or pipes while you drive
- Sets in 30 minutes
- · Not affected by vibration
- 170g





### HI-TEMP RED GASKET MAKER

 Withstands repeated hot and cold cycles from -60°C to 315°C (-75°F to 600°F)

#	Color	Size	V
474	Red	85 g	N. Carlot
477	Red	300 ml	
Moon dib	201		1000
	KLF		



### SILICONE GASKET MAKER

 Withstands temperatures from -57°C to 260°C (-70°F to 500°F)

#	Color	Size
470	Black	85 g
471	Black	300 ml
472	Clear	300 ml



20 I KLF

**QUICKTITE® INSTANT** 

 Self-piercing tip and locking cap Improved dispensing control & accuracy

**ADHESIVE GEL** 

Spill proof design

### 401™ PRISM® ADHESIVE

- Instant cyanoacrylates adhesive for the most stringent demands
- Ideal for gap-filling applications and provide
- · Fast, strong bonding on rough, porous, and acidic surfaces
- Temperature range of -65°F to 180°F
- Tensile shear strength of between 2,600 and 3,200 PSI
- 20 g



# 40140 220 HEN



LOCTITE

### 404™ QUICK SET INSTANT ADHESIVE

220 **HEN** 

- For general maintenance and repair, one part, room temperature cure
- Excellent for bonding rubber and frequently used for rubber O-ring bonding
- 1/3 oz

# 46551

# 39202







- · Designed to bond rubber, metal, and plastic parts with gaps to .004"
- | oz







### FIXMASTER® METAL MAGIC STEEL™ EPOXY

- Steel epoxy in stick form
- Cures in 10 minutes
- Certified and approved for use with drinking water system components

4 oz

# 98853



220 HEN

### **QUICK GEL® SUPER GLUE**

• 2 g



LOCTITE

HEN



### **HIGH FLEX FORM-IN-PLACE** ANAEROBIC GASKET

• 50 ml

# 38628



220 HEN



### O-RING MAKING KIT

Makes replacement, high performance o-rings in less than a minute. Includes:

- I oz waterproofing solution
- · I oz clean-up solvent
- I/3 oz 404™ Quick Set™ instant adhesive
- O-Ring Cord 3/32", 1/8", 3/16", 1/4"
- Fixture and cutting blade

# 00112



HEN

## POXY-PAK™ EPOXY

- · Fast cure, general purpose epoxy, bonds virtually any material
- · Will also fill or seal cracks and rebuild worn surfaces.
- 4-minute cure time
- I oz

# 1324007



220 HEN

### 518™ ANAEROBIC **GASKET MAKER**

• 50 ml

# 38638



220 HEN



### **READY GASKET -AEROSOL GASKET MAKER**

- OEM specified product used in Ford, GM and Chrysler OE engine production facilities
- Extreme chemical resistance to hot oil and temperature resistant to 500°F (intermittent)
- 190 ml

# 40480





### KLEAN 'N PRIME™

- Activator for anaerobic adhesives
- 4.5 oz

# 38611







### 609™ RETAINING COMPOUND

- Low viscosity, rapid-curing anaerobic adhesive that augments the strength of press fit assemblies or slip fit assemblies up to 0.006" in diameter
- Adds up to 3,000 PSI holding power
- · Recommended for parts that will need subsequent dismantling

<del>.</del> #-	Size	
60921	10 ml	1
60931	50 ml	WHAT I
LOCTITE	220	#@C7/7# 609
	HEN	608 - J

### 680™ RETAINING COMPOUND

- High strength, room-temperature curing adhesive used to join fitted cylindrical parts.
- Provides shear strength of 4,000 PSI after 24 hours.
- Fills gaps up to 0.015" (0.27 mm).
- · Allows relaxed machining tolerances and replaces clamp rings, set screws, and snap rings
- 50 ml



### **RTV BLACK SILICONE**

- · Seals/bonds/mends glass, metal, plastic, fabric and rubber
- Temperature resistant to 450° F
- · Resistant to oil, water, weather and vibration
- 300 m



• 80 ml

# 38616

RTV 587™ BLUE SILICONE




220 HEN





220 HEN

### **RTV CLEAR SILICONE**





220 HEN



### **RTV RED SILICONE**

- · Sensor-safe/hi-temperature gasket maker
- 300 ml





220 HEN

### RTV 5699™ GREY SILICONE

- · High-performance gasket maker
- 80 ml

# 38633 LOCTITE 220



### RTV 5920™ COPPER SILICONE

· High Performance Gasket Maker

#	Size
38639	80 ml
38640	300 ml



220 HEN



### 242® THREADLOCKER

 Medium strength general purpose, removable thread locker for fasteners between 1/4" and 3/4" (6 to 20 mm) diameters

50 ml

# 24231



220 HEN



### 243™ THREADLOCKER

- Medium strength/oil resistant removable grade threadlocker
- Protects threaded parts from vibration, loosening and corrosion
- For fastener diameters of 1/4" to 3/4"

#	Size
1330902	6 ml
1330906	36 ml
1329467	50 ml



220 HEN



### QUICKTAPE™ 249™ MEDIUM STRENGTH THREADLOCKER

- No mess and no waste!
- Same reliability and performance as removable grade threadlocking liquids
- 1/2" × 260"





220 HEN



### **262™ PERMANENT THREADLOCKER**

#	Strength	Size
26231	Med/High	50 ml
38637	High	6 ml
38647	High	36 ml



220 HEN



### PST® 565™ THREAD SEALANT

- · High performance sealant
- 50 ml

# 38635



220 HEN



### PST® 592™ THREAD SEALANT

- High temperature
- 50 ml

# 38613



220 HEN



### 271™ HEAVY-DUTY THREADLOCKER

#	Size
38623	6 ml
38624	36 ml
38625	50 ml



220 HEN



### PST® 567™ THREAD SEALANT

- Locks and seals metal, tapered pipe threads and fittings
- Ideal for stainless steel, aluminum, galvanized metal, and other inert metals
- 50 ml

# 56747







### **BLUE/ RED STICK THREADLOCKER**



#	Description	Size
38131	Blue - Medium Strength	19 g Stick
38132	Blue - Medium Strength	9 g
38134	Red - High Strength	19 g Stick
38136	Red - High Strength	9 g





### BLACK WEATHERSTRIP ADHESIVE -FAST DRYING

- Perfect for attaching weather-stripping, carpet, and other common materials
- Withstands extreme temperatures and resists gasoline, kerosene, antifreeze, and most solvents
- 5 oz

# AUTOMOTIVE GLOOZIT®

- Repairs vinyl tears on car seats, floor mats, and convertible tops
- Seals leaks in hoses, treads, windshields and headlights
- Protects battery terminals against corrosion
- · Insulates electrical wiring
- 90 ml





### MARINE/RV GLOOZIT®

- Weatherproof adhesive and sealant that protects and prolongs seals; secures, renews and repairs
- 90 ml



### INDUSTRIAL GLOOZIT™ ADHESIVE

 Remains flexible after curing and withstands expansion and contraction of dissimilar materials. Bonds to virtually everything

90 ml



### SHOE GLOOZIT™ ADHESIVE

- · Repairs holes in seams and soles
- Reattach heels, lock-in spikes on golf shoes, create a pitcher's toe, repair skate boards and inline skates, toes on hockey skates, goalie pads, gloves and equipment, rubber boots, hip waders, wet suits, etc.
- 90 ml



# TECHSTEEL® EPOXY PUTTY

- · Molds like clay and hardens like steel
- Repairs ferrous and aluminum metals, fill cracks and seal leaks
- Form nuts and bolts and repair stripped threads
- Will not rust or shrink

#	Size	NLS PRODUCT
6002	2 oz	100
6004	4 oz	
		487
3000 2000	ECH-STEEL III	NLS

## TECHSTEEL EPOXY PUTTY

- Permanently adheres to steel, aluminum, wood, copper, cast iron, PVC, ABS, bronze, concrete, plastic, glass, fibreglass, ceramics and brass, even under water
- 500°F temperature resistant
- Impervious to chemicals
- Steel hard in 15 minutes, full cure in 1 hour
- 2 oz



# 16002



487 NLS

### CLEAR VINYL REPAIR LIQUID

 Provides a strong permanent repair to all vinyl products

28 ml

# 7625



487 NLS



### HEAVY DUTY ADHESIVE SPRAY

- Dries clear
- VOC compliant
- Applications: headliners, carpets, trunk linings and door panels.
   For use on foam, fabrics, plastics and rubber
- 474 g

Permatev



### PIPE JOINT COMPOUND

 Lubricates and seals threaded joints on water, oil and fuel lines

# 80045

16 oz

Permater 203



## INSTA-FIX PRO ADHESIVE AND FILLER SYSTEM

- Instant permanent bond to virtually any surface, holds up to 800 lbs
- Sandale, paintable, 100% waterproof
- 20 g

# PFK20G

313

PHX

## REARVIEW MIRROR ADHESIVE

- Approved and used by GM, Ford and Chrysler
- Permanently remounts mirrors to windshields

# **Size**3306 0.9 ml



203



### SUPER WEATHERSTRIP ADHESIVE

- Ideal for many applications including rubber, metal, auto or van carpeting and fabric-backed vinyl upholstery and automotive gaskets
- 59 ml

# 80BR



203



## COLD WELD BONDING COMPOUND

- A 15-minute, two-part adhesive and filler system
- Over 3,000 PSI shear strength on steel

# 14600





## •

### **ULTRA BOND™ SUPER GLUE GEL**

- Gel formula works better on more porous materials
- Applications: rubber, metal, wood, ceramic, porcelain, leather, vinyl, paper, cork, fabric and most plastics
- 2 g



# 30030



### ULTRA BOND™ SUPER GLUE

• Outperforms regular super glues

#	Size
49502	3 ml
49512	28 g







# PERMAPOXY™ 5-MINUTE GENERAL PURPOSE EPOXY

- · Sets in five minutes
- · Fills gaps and will not shrink
- Permanent strength up to 3,400 PSI





# PERMAPOXY™ 4-MINUTE MULTI-METAL EPOXY STICK

- Fast setting putty
- Can be drilled, machined, filed, painted
- Permanent strength up to 3,500 PSI

• 59 ml

# 25832



203



## PERMAPOXY™ 5-MINUTE PLASTIC WELD

- Forms a tough, durable bond to most plastics, composites, ceramics, wood in any combination
- NOTE: Will not bond most polyethylene or polypropylene plastics
- Permanent strength up to 3,500 PSI
- 25 ml



# 84125 **203** 



### PERMAPOXY™ 4-MINUTE MULTI-METAL EPOXY

- Fast setting epoxy in an easy to use 2-part dispensing syringe
- Better choice than super glues for bonding parts with larger gaps
- Permanent strength up to 4,500 PSI
- 25 ml



### PERMAPOXY™ I-MINUTE CLEAR EPOXY

- · Easy to use 2-part dispensing syringe
- Better choice than super glues for bonding parts with larger gaps
- Permanent strength up to 2,500 PSI
- 25 ml

# 84162



203




### **FAST CURE EPOXY MIXER CUPS**

- · Fast setting, grey epoxy in a unique, easy to use mixer cup
- Bonds in 5 to 15 minutes
- 10 x 4 g cups



### **FORM-A-GASKET®** NO. I SEALANT

- For dressing/sealing cut gaskets on rigid flanges
- USA Mil-S-45180 D, Type I
- 80 ml



### **FORM-A-GASKET® NO. 2 SEALANT**

- · Slow-drying, non-hardening sealant designed for sealing cut gaskets and stamped parts
- · Allows for easy disassembly if required
- || oz



### **FORM-A-GASKET® NO. 2 SEALANT**

- · Slow-drying, non-hardening sealant
- 80 ml



### **FORM-A-GASKET®** NO. 3 SEALANT

- · Slow-drying, non-hardening brush-top sealant approved for use in aviation as well as automotive applications
- · 16 oz



### **AVIATION FORM-A-GASKET®** NO. 3D SEALANT

 Slow-drying, non-hardening brush-top sealant

180 ml





### **ULTRA BLUE® MULTIPURPOSE** RTV SILICONE GASKET MAKER

- · Sensor-safe, low odor, noncorrosive
- · Three times higher oil resistance than conventional silicones
- · Eight times more flexible than cork/composite gasket

than convenience gasic	
#	Size
77BR	80 ml
77C	300 ml
Permates	202



### **ULTRA BLACK® MAXIMUM OIL RESISTANCE RTV SILICONE GASKET MAKER**

- Ensures extended drive train warranty compliance
- Sensor safe, low odor, noncorrosive
- Meets performance specs of OE silicone gaskets

#	Size
59803	80 ml
59813	300 ml







### **ULTRA COPPER® MAXIMUM TEMPERATURE RTV SILICONE GASKET MAKER**

- OEM specified
- Highest operating temperatures for 4-cylinder, turbocharged or high-performance engines
- Sensor-safe, noncorrosive

#	Size
IOIBR	80 ml
101C	300 ml
Permates	203



### **ULTRA GREY® RIGID HIGH-TORQUE RTV SILICONE GASKET MAKER**

- For high-torque and high vibration applications
- Non-corrosive
- Maximum vibration resistance
- Guaranteed not to leak.

#	Size
82194	80 ml
82195	300 ml



203





### SENSOR-SAFE RTV SILICONE **GASKET MAKER**

- Will not foul oxygen sensors
- Formed-in-place gaskets
- · Resists cracking, shrinking and migrating



#	Size	Color
17BR	80 ml	Noir
17C	300 ml	Noir





### **BLUE RTV GASKET MAKER**

- · Use for sealing, bonding, insulating, caulking, making gaskets and coating pre-cut gaskets
- Designed for use on pre-1980 engines

203

#	Size
6BR	80 ml
6C	300 ml

Permatev



### THE RIGHT STUFF® **I-MINUTE GASKET**

- Seals instantly
- Non-fuel sealing applications
- Superior to most OE
- Protects against leaks caused by vibration and thermal expansion
- Sensor-safe.

Size
147 ml
$2 \times 147 \text{ ml}$
212 g



203



### THE RIGHT STUFF® **GASKET MAKER**

- Short caulking gun
- · Elastomeric rubber gasket technology is blowout resistant and outperforms pre-cut
- · Specified on production lines by GM, Ford, Chrysler and Mercedes-Benz

• Sensor-safe



### MOTOSEAL™ I ULTIMATE **GASKET MAKER, GREY**

- · Forms a tough flexible film for high reliability sealing
- · Best for parts that require frequent disassembly
- 80 ml

# 38401





### SUPER HIGH TACK™ **GASKET SEALANT**

- Tacky paste for holding cut gaskets in place during assembly
- Helps seal cut gaskets
- 118 ml



### ANAEROBIC GASKET MAKER

- · Use for gasketing close fitting rigid-machined flanges with gaps up to 0.25 mm (0.01") unprimed; 1.27 mm (0.05") with primer
- Applications: water pumps, thermostat housings, transmission pans, transmission case covers, transaxle casings, o-ring replacement.
- 50 ml

# 51813



203

### **GEAR OIL RTV GASKET MAKER**

- OEM specified sealant formulated to withstand friction modifiers found in synthetic gear oil
- · Used on differentials and ransfer cases
- Sensor-safe

# 31872



203



### **GASKET REMOVER**

- Quickly removes all solvent-based gasket adhesives and sealants
- 340 g

# 4MA



203



### **INDIAN HEAD® GASKET SHELLAC COMPOUND**

- Seals all common gasketing materials in low temperature and low pressure applications
- Applications: hose connections, paper and cardboard gaskets
- 50 ml



# 5J-1



### **MAXIMUM TEMPERATURE** SLEEVE RETAINER

- OEM specified
- · Bonds cylindrical parts with diametric gaps up to 0.015" (0.35 mm)
- · Provides shear strength of 3,800 PSI on steel
- 36 ml





### **HIGH TEMPERATURE** THREAD SEALANT

- · Locks and seals threaded fittings
- · Resists leakage, vibration loosening, moisture, hydraulic fluids and diesel fuels
- Contains PTFF

#	Size	
59214	6 ml	
59234	50 ml	







### **RED HIGH STRENGTH THREADLOCKER**

- OEM specified
- High strength threadlocker for heavy-duty applications for locking fasteners 3/8" to 1" (10 mm to 25 mm)
- · Adds 3,000 PSI holding power on slip and press fit assemblies
- · USA Mil-Spec (S-46163A) Type I, Grade K

#	Size	
27115	10 g	
27140	36 ml	



203

### **HIGH PERFORMANCE** THREAD SEALANT

- Replaces Teflon® tape and pipe dopes
- Contains PTFE

#	Size
56521	50 ml
© Permates	203



### THREAD SEALANT WITH TEFLON

- · Seals and resists pressure in air, oil, diesel fuel and hydraulic systems
- 118 ml





### **HIGH STRENGTH** THREADLOCKER RED

- · High strength threadlocker for heavy-duty applications, for locking fasteners 3/8" to 1"
- (10 mm to 25 mm) • 7 g

# 31876





### HIGH TEMPERATURE THREADLOCKER RED

- · OEM specified.
- High temperature/high strength threadlocker for 3/8" to 1-1/2" (10 mm to 38 mm)
- 10 ml

Permates 203



# PERMANENT STRENGTH RED THREADLOCKER

 Adhésif frein-filet permanent à adhérence permanente pour les pièces de fixation de 10 à 25 mm de dimension.

#	Size
26200	6 ml
26210	I0 ml
26240	36 ml
26250	50 ml
26225	250 ml





### MEDIUM STRENGTH BLUE THREADLOCKER

• Medium strength threadlocker for fasteners 1/4" to 3/4" (6 mm to 20 mm)

#	Size	
31878	0.5 ml	
24200	6 ml	
24210	10 ml	
24215	10 g	
24240	36 ml	
24250	50 ml	



203



### THREADLOCKER GELS IN THE GEL TWIST & GEL SQUEEZE APPLICATORS

- Medium Strength BLUE Gel in a GELTWIST™ pin-point applicator
- · No drips, no globs, no mess and no waste
- 5 g







# BLUE SURFACE INSENSITIVE THREADLOCKER

- OEM specified
- Medium / high strength threadlocker for fasteners 1/4" to 3/4" (6 mm to 20 mm)
- 50 ml



# PENETRATING GRADE GREEN THREADLOCKER

- OEM specified
- Low viscosity threadlocker from less than or equal to 1/2" (12 mm)
- USA Mil-Spec (S-46163A) Type III, Grade R







# BEARING MOUNT FOR WORN PARTS

- OEM specified
- Used between parts to repair large gaps and severely worn parts
- 3,000 PSI holding power
- Fills gaps to .020" in diameter
- 6 ml





### **PRUSSIAN BLUE**

- Locates high spots on shafts, valves, gears and other close tolerance components
- 22 ml

# 35V



203



### RED HIGH TEMPERATURE RTV ADHESIVE SEALANT

- Seal and waterproof electrical connections, firewall openings, heater boxes
- Seals and bonds glass, metals and plastics

Size
80 ml
300 ml





LICON RT

26C

# 203

### CLEAR RTV SILICONE ADHESIVE SEALANT

 Seals, bonds, repairs, mend and secure glass, metal, plastics, fabric, vinyl, weather stripping and vinyl tops

 Protects and repairs electrical wiring

#	Size
66BR	80 ml
66C	300 ml



203



### ANAEROBIC FLANGE SEALANT

- For use on rigid machined flanges with less than .015" gap
- OEM approved

# **Size**51531 50 ml



203



### BLACK SILICONE ADHESIVE SEALANT

- Seals, bonds, repairs, mend and secure glass, metal, plastics, fabric, vinyl, weather stripping and vinyl tops
- Protects and repairs electrical wiring

Size
80 ml
300 ml



203



### HIGH TACK™ SPRAY-A-GASKET™ SEALANT

- Fast-drying sealant dries to a highly tacky, non-brittle film
- Level 3Niveau 3

#	Size	
99MA	255 g	



203



### COPPER SPRAY-A-GASKET™ HIGH-TEMP SEALANT

- · Resists all types of automotive fluids, especially gasoline
- Applications: cylinder head gaskets, carburetor gaskets, exhaust manifold gaskets and other high temperature applications
- 283 g

# 101MA



203





### SUPER WEATHERSTRIP ADHESIVE

- A superior adhesive ideal for many applications including rubber, metal, auto or van carpeting and fabric-backed vinyl upholstery and automotive gaskets
- 5 oz



# 81731



### **MUFFLER & TAILPIPE**

- Epoxy-impregnated fibreglass bandage chemically welds mufflers and tailpipes
- Permanently repairs holes and leaks in exhaust systems saving costly part replacement
- Seals out poisonous fumes to temperatures of 800°F (426°C)



#	Description
80331	84 sq. in. Bandage
80333	4 oz (2 foil pouches)
80335	3 oz tube



# EXHAUST SYSTEM REPAIR KIT

 Makes lasting and permanent repairs to holes, cracks and leaks in mufflers, exhaust pipes and catalytic converters







### PLASTIC TANK REPAIR KIT

- Quick permanent repairs to plastic tanks (not for use on plastic FUEL tanks)
- Repairs cracks up to 4" (10 cm) long and holes up to 3/8" (9 mm) in diameter

# 09220





# REAR WINDOW DEFOGGER REPAIR KIT

 Re-bond rear window defogger tab and repair defogger grid lines.







# BULLSEYE™ WINDSHIELD REPAIR KIT







### **BRÄKLEEN® NON-FLAMMABLE BRAKE PARTS CLEANER**

· Formulated to quickly & effective remove grease, brake dust, brake fluids, oils, & other contaminants from brake parts, lining, pads



#	Format
75089	539 g
75090	9.785 L
7509 I	19 L





### **BRÄKLEEN® NON-CHLORINATED BRAKE PARTS CLEANER**

 Use when compliance calls for a chlorine-free product

• 397 g

# 75088




218 CRC

### **BATTERY TERMINAL PROTECTOR**

- · Provides a lead-free soft protective coating
- · Protects battery terminals from corrosion, a leading cause of hard starting and battery failure
- 213 g

CRC

# 75046 218 CRC



- Forms a water resistant, high-temperature film that absorbs noise, while quieting squeaks & squeals
- Dampens vibrations
- · Backing plates, brake pad contact points, disc brake pads
- 118 ml

#	Description	
75016	II8 ml	1
75017	Aerosol 225 g	The state of
CRC	218	Siles
	CRC	8



### **BATTERY CLEANER** WITH ACID INDICATOR

- · Instantly detects leaks and neutralizes acid
- Removes corrosion by-products
- · Battery terminals, battery casings, cable connectors & hold downs
- 312 g

# 75097



- · Re-liquefies gelled fuel in minutes!
- Totally disperses water and lowers pout point by as much as 35°F
- · Prevents future gelling since it contains anti-gel
- 946 ml





### **IUMP START STARTING FLUID**

218

CRC

- · Assure fast, economical starts in cold or humid conditions
- · Contains an upper cylinder lubricant to minimize wear during cold starts
- Use in gasoline & diesel engines
- 312 g

# 75671 218 CRC





### **BRAKE CALIPER** SYNTHETIC GREASE

- High temperature grease is plastic & rubber safe
- Use on metal to metal contact points and sliding surfaces
- · Resists moisture and will not washout
- 340 g

# 75353 218





### **ZEREX® ORIGINAL GREEN** ANTIFREEZE/COOLANT

- Low-silicate chemistry for heavy-duty applications with use of SCA
- Excellent aluminum protection
- 3.78 L

210 VAL



### **ZEREX DEX-COOL®** ANTIFREEZE/COOLANT

- Protection for up to 5 years / 150,000 miles
- GM DEX-COOL Approved
- Navistar CEMS B-1 Type IIIA
- Organic Acid Technology (OAT) minimizes corrosion inhibitor depletion
- · Patented formula contains no silicates, phosphates, borates, nitrates or amines
- 3.78 L

# 575284



210 VAL



### AIR SHIELD™ DIESEL EXHAUST **FLUID (DEF)**

- · API and AdBlue certified
- Meets ISO22241 specifications

#	Format
728770	3.78 L
729566	$2 \times 9.45 L$
728802	1,249 L
749714	208 L



210 VAL



### **ZEREX® EXTENDED LIFE** ANTIFREEZE/COOLANT

- Fully formulated or pre-charged to protect against liner pitting and hard water scale
- · Meets the Caterpillar EC-1 long-life spec., Cummins 14603 approved
- Extend drain interval to 6 years, 14,000 hours, or 600,000 miles with the use of Zerex® Extended Life Extender
- 3.78 L

# 3495



210 VAL



### ZEREX™ 50-50 PREDILUTED **READY-TO-USE ANTIFREEZE COOLANT ZXRUI**

3.78 L

# 505841



210 VAL



### ZEREX G-05® ANTIFREEZE/COOLANT

- Protection for up to 5 years / 150,000 miles
- · Approved by Ford and DaimlerChrysler for use in automotive and diesel engines
- · Utilizes hybrid organic acid technology to minimize inhibitor depletion
- · Low-silicate, low-pH and phosphate-free formula

#	Format
3477	3.78 L
3658	208 L



210 VAL





### **BRAKE FLUID**

 For drum, disc and ABS braking systems, and clutch systems







۱۸*۱*. .



#	Grade	Format	Boiling Point	Boining Point
525	DOT 3	350 ml	246 °C (475 °F)	140 °C (284 °F)
527	DOT 3	500 ml	246 °C (475 °F)	140 °C (284 °F)
528	DOT 3	ΙL	246 °C (475 °F)	140 °C (284 °F)
529	DOT 3	4 L	246 °C (475 °F)	140 °C (284 °F)
530	DOT 3	20 L	246 °C (475 °F)	140 °C (284 °F)
532	DOT 4	350 ml	246 °C (475 °F)	140 °C (284 °F)
535	DOT 5	350 ml	315 °C (600 °F)	N/A

### **BRAKE-IN**

- Revolutionary Brake-In prevents brake noise at the source
- Effective on all brake systems, no drying time required
- Temperature use range -100°C to 1000°C
- 225 g

# 333



201 KLF



### **EZE-SLIDE**

- Silicone-based brake lubricant for extreme operational temperatures
- Prevents corrosion of sliding caliper pins to keep brake pads from wearing unevenly
- 170 ml

# 331



201 KLF



### **DISC BRAKE QUIET**

- Designed to eliminate disc brake squeals caused by vibrations of the brake pad
- Extreme temperature and water resistant film protection
- Dampens and absorbs chatter and vibration
- 118 ml



201 KLF





### **BRAKE & ELECTRICAL CONTACT KLEEN**

- Non-conductive for cleaning electrical equipment including alternators, distributors, dynamos, switches, relays, regulators and small electric motors
- Suitable for air brake components
- Non-flammable
- 672 g



201 KLF





### SAFE-T-BRAKE AIR BRAKE ANTI-FREEZE

- · Absorbs condensation and ensures complete protection against frozen air lines on trucks, buses, and construction equipment
- Contains Anti-corrosive agent to protects all steel, rubber and brake line parts against corrosion and to minimize wear



201 **KLF** 

#	Format
509	950 ml
510	4 L

· Safely neutralizes sulphuric acid spills on skin,

• Effectively removes dust and prevents

20 I KLF

**BATTERY ACID NEUTRALIZER** 

self discharge rate

• 198 g

clothing and battery box



### **KLEEN-START STARTING FLUID**

Priming fluid formulated to spray at extreme sub-zero temperatures.

# 730

- Effective to -53C (-63°F)
- · Instantly starts all types of gasoline and diesel engines
- · Contains an upper cylinder lubricant to reduce dry-start
- 211 g



# 445



Hosen	
410	20 I
	KLF
7	

### **ACE STARTING FLUID**

- · Licensed ether product to start all types of gasoline and diesel engines
- · Contains an upper cylinder lubricant to reduce dry-start engine wear
- · Increases starter and battery life
- Effectively works at temperatures to 51°C
- 221 g



20 I **KLF** 



### **BRAKE & PARTS KLEEN**

- · Removes brake fluid, oil, grease, transmission fluid, brake dust and other contaminants from all types of brake assemblies
- · Dries quickly leaving no residue
- · Low odour



20 I KLF

#	Format
313	390 g
322	4 L
323	20 L







### **EXTENDED LIFE ANTIFREEZE/COOLANT**

- Compatible with ANY antifreeze/coolant in ANY vehicle with aluminum and other engine metals
- Can be re-inhibited using Supplemental Cooling Additives (SCA) (for topping off conventional coolants) or Extender (when used with other extended life HD coolants)
- Low dissolved solids



#	Format
11551	3.78 L
11568	205 L



### PREMIXED EXTENDED LIFE ANTIFREEZE/COOLANT

- Compatible with ANY antifreeze/coolant in ANY vehicle with aluminum and other engine metals
- Mixes with ANY colour antifreeze/coolant
- 3.78L



271 PRA # 11576



27 I

PRA

# DEX.COOL® APPROVED LONGLIFE® ANTIFREEZE/COOLANT

- Cooling system protection for five years or 240,000 km
- Aluminum compatible
- Silicate and phosphate-free
- · Compatible with other extended life coolants
- Recommended and formulated for use in all GM vehicles that require DEX•COOL® antifreeze/coolant as well as all other cars and light duty trucks with aluminum radiators
- Meets or exceeds all ASTM and SAE standards for coolant corrosion protection
- 3781

# 71118



# LOW TOX® ANTIFREEZE/COOLANT

- Propylene glycol based
- Meets or exceeds ASTM industry protection standards
- Added margin of safety for pets and wildlife in the event of accidental ingestion
- 3.78 L

# 70052





# LONGLIFE™ ANTIFREEZE/COOLANT – "ALL MAKES" FORMULA

- Traditional colour is compatible with ANY antifreeze/coolant
- · Premium long-lasting inhibitors
- Provides up to 5 years or 250,000 km of protection
- Protects against temperature extremes, rust, corrosion and premature water pump failure
- 3.78 L







### "ALL MAKES" LONGLIFE® ANTIFREEZE/COOLANT

- · Compatible with ANY antifreeze/coolant
- 50% antifreeze/coolant and 50% demineralized water
- 5 years or 250,000 km protection when added to ANY extended life or LongLifeTM antifreeze/coolant
- 3.78 L



# 71175



# HEAVY-DUTY DIESEL EXTENDED LIFE ANTIFREEZE/COOLANT (ELC)

- Compatible with ANY heavy duty antifreeze/coolant in ANY diesel powered truck, farm, off-road, marine or gasoline engine with aluminum and other engine metals.
- TMC compliant colour
- · Premium long-lasting inhibitors
- Provides up to 480,000 km or 6,000 hours of protection against temperature extremes, rust, corrosion, scale, and premature water pump failure
- 3.78 L



PRA

# 71316



# SCA PRE-CHARGED HEAVY-DUTY ANTIFREEZE/COOLANT

- A blend of Ethylene Glycol and a specially formulated inhibitor package designed for heavy duty cooling system applications
- Designed to eliminate the initial charge of supplemental coolant additive (SCA) on new vehicles and recharged systems
- 3.78 L



271 PRA # 72702



# PREMIXED HEAVY-DUTY DIESEL EXTENDED LIFE ANTIFREEZE/COOLANT (ELC)

- Compatible with ANY heavy duty antifreeze/coolant in ANY diesel powered truck, farm, off-road, marine or gasoline engine with aluminum and other engine metals
- Premium long-lasting inhibitors
- 50/50 blend of antifreeze and demineralized water
- Protection up to 480,000 km or 6,000 hours when added to ANY ELC type heavy duty antifreeze/coolant
- 3.78 L



PRA





### **UNIVERSAL 50/50 PREMIX ANTIFREEZE/COOLANT**

- · Protects against winter freezing and summer boil over
- Prevents pitting caused by cavitation and corrosion of brass, copper, solder, steel, cast iron and aluminum
- Low silicate
- Aluminum compatible
- · Premixed -

DO NOT ADD WATER

• 18.9 L



424 REC # 16-422



### **EXTENDED LIFE 50/50 PREMIX ANTIFREEZE/COOLANT**

- 250,000 km or 5 years service life protection in automotive
- ASTM D-3306, Japanese Standard JIS K2234, Ford WSS-M97B44-D, GM 6277, VWTL 774D
- 3.78 L



424 **REC** 

# 16-104



### **TURBO POWER® DOT 3 BRAKE FLUID**

- · Controls elastomer swell thereby ensuring efficient seal performance and provides the required lubricity to all moving parts
- Meets the performance requirements of FMVSS-116, and SAE J1703

424
REC

#	Format	
15-813	350 ml	
15-810	500 ml	
15-811	ΙL	
15-814	13.78 L	
15-818	20 L	



### **AUTOXTRA® UNIVERSAL RADIATOR ANTI-FREEZE**

- Prevents pitting caused by cavitations and corrosion of brass, copper, solder, steel, cast iron and aluminum
- ASTM D-3306, D-4985, DaimlerChrysler MS7170, Ford ESE-M97B44-A, GM 1825M, 1899M, TMC RP 302B
- · Low silicate, aluminum compatible
- 3.78 L



424 REC



### **DIESEL FUEL CONDITIONER**

- · Removes moisture & cleans fuel system
- · Prevents & thaws frozen fuel lines
- · Helps remove gum and sludge from entire fuel system
- | L









### **AIR1® DEF DIESEL EXHAUST FLUID**

- · Pure, aqueous solution of urea and water, to be used in new diesel SCR engine technology; it is API certified and meets ISO 22241 standards
- · Required in trucks using SCR technology, DEF helps reduce emissions of NOx gases that are produced inside the engine during combustion

#	Format
55-124AIR	3.78 L
55-125AIR	9.46 L



424 **REC** 



### **AIR BRAKE ANTIFREEZE**

- · Prevents frozen air lines during winter temperatures
- · Contains lubricants to minimize wear of valves and seals
- Readily absorbs condensation within the air brake systems
- Methanol-based for fast results

Format
l L
3.78 L



424 RFC



### **AUTOXTRA® WINDSHIELD WASHING FLUID**

- -40 °C
- 3.78 L

# 00001



424 **REC** 



### WINDSHIELD WASHER

- - 40°
- 4 L

# 15-215X52



424 REC



### **RAIN-X® BUG & TAR REMOVER WINDSHIELD WASHER**

- Special warm weather solution cuts through bugs, grime, oil and dirt to guickly restore clear vision
- 3.78 L



424 **REC** 

# 35-414QS



### **RAIN-X® DE-ICER** WINDSHIELD WASHER

- -40 °C
- 3.78 L

# 35-204QS



424 REC



### **RAIN-X® ALL SEASON** WINDSHIELD WASHER

- -40 °C
- 3.78 L

# 35-303QS







# BATTERY TERMINAL PROTECTOR

 Coats battery terminal, holder hardware and prevents battery acid corrosion

# BTP4C



205 RAD



### NON-CHLORINATED BRAKE CLEANER

- Quickly dissolves and flushes away surface contaminants such as brake fluid, oil, and grease from brake linings, drums, other brake parts and CV joint assemblies
- 390 g

# M705C



205 RAD



# SUPER HEAVY DUTY DOT 4 BRAKE FLUID

- For vehicles with disc or drum brakes
- Used for heavy-duty equipment and recommended by several manufacturers of automotive, brake, and farm equipment
- 350 ml

# M4512C



205 RAD



### **BRAKE CLEANER**

- It leaves no residue and helps stop disc brakes squeal and chatter
- 510 g





# BATTERY TERMINAL CLEANER

- Cleans battery terminals, connectors, battery tray and holder bolts and brackets by neutralizing acid corrosion
- |4| g

# BTC4C



205 RAD



### LIQUID FIRE STARTING FLUID

- Produces quick, smooth starting of gasoline and diesel engines under extreme cold conditions down to -53° C
- 350 ml

# M3911C



205 RAD



### **SUPER HEAVY DUTY DOT 3 BRAKE FLUID**

- Meets or exceeds Canadian Motor Vehicle Safety Standard #116, Society of Automotive Engineers Standard J1703, and meets GM, Ford, and Chrysler OEM standards
- 350 ml



205 RAD # M4312C





### **AIR BRAKE SYSTEM ANTI-FREEZE AND RUST GUARD**

- Disperses water
- · Anti-static, anti-fungal
- · Provides corrosion protection
- | L

# M2832/6C



205 RAD



### **AIR BRAKE ANTI-FREEZE**

- Contains rubber lubricant
- 32 oz

M2834C 205



### **DIESEL FUEL ANTI-GEL** AND CONDITIONER

- Prevents gelling
- Lowers pour point to -40°C
- 946 ml

# M6932C



## **DIESEL FUEL CONDITIONER** & ANTI-GEL

RAD

- · Lubricates and lowers gelling up to 15°C below base fuel
- Absorbs water
- 946 ml

# M7232C carburani 205 RAD



205 RAD

### **DIESEL FUEL DE-GEL**

• Dissolves gelled Diesel fuel in 15 minutes

205 **RAD** 

- For low or high sulfur diesel fuel
- No ash build-up
- 946 ml





### **EXTREME COLD FUEL** TREATMENT WITH ANTI-GEL

- Prevents fuel thickening
- · One half gallon will treat 250 gallons of fuel
- I quart

#	Format
20012 20021	l quart I/2 gallon
Wess or other	277

LUC



### **BATTERY CHEMICALS & LUBRICANTS**

· Application-specific formulation

#	Description	Format
278	Battery Terminal Protector	340 g
279	Battery Cleaner	340 g
281	Dry Graphite Lubricant	312 g



387 **PKP** 









### **ULTRA DISC BRAKE CALIPER LUBE**

• Non-melting, synthetic lubricant



#	Forma
31877	5 g
22063	80 ml
09125	236 g







### **NON-CHLORINATED BRAKE & PARTS CLEANER**

- Penetrates, dissolves and removes dirt and oil from brake systems and metal parts
- Safe for aluminium



# 29213



### **DISC BRAKE QUIET**

- Stops brake squeal by dampening vibration at caliper/brake pad interface
- 255 g



# 127MA



### **BATTERY CLEANER**

- Penetrates and removes corrosion, dirt and grime instantly
- 163 g

Permates





# BATTERY PROTECTOR & SEALER

- Coats and seals battery terminals to prevent corrosion
- |4| g



# SA-9



### **BATTERY PROTECTOR**

Coats and seals battery terminals to prevent corrosion







### MINIMAL **EXPANSION FOAM**

- · Fill, seal, bond, retrofit, insulate and deaden sound in and around cracks and cavities
- Forms a permanent, waterproof and airtight bond to most surfaces
- UL classified as a caulking sealant
- 454 g aerosol





218 CRC

### PERM-O-SEAL RADIATOR **STOP LEAK, GRANULES**

- · For use with radiator/coolant system leaks
- · Specific gravity less than I
- 0.07 oz



JBW

### **HYDRAULIC OIL BOOSTER & STOP LEAK**

- Stops leaks
- · Prevents major overhauls
- Reduces heat

#	Size
20018	l gallon
20019	l quart



277 LUC



### **VALVE GRINDING** COMPOUND

• 115 ml

# 474G





### SPRAY SEALANT

- Sprays on to form a clear durable rubber barrier, eliminates need for liquid additive sealers
- Fills gaps up to 0.04".
- · Adheres to metals, rubber, glass, masonry, wood and most plastics
- 255 g



### **ENGINE OIL STOP LEAK**

Dermates'

- Compatible with petroleum, semi-synthetic and full synthetic motor oils
- · Renews worn seals with no risk of damage or eventual corrosion

#	Size
20278	l quart
20279	I gallon



277 LUC



### POWER STEERING STOP LEAK

- GUARANTEED to stop seal leaks in power steering units
- Reduces slack, squeals, and hard spots in worn rack and pinions



#	Size
20008	12 oz
20011	l quart





# RAD SEAL RADIATOR STOP LEAK

- Powdered metallic sealer designed to instantly seal leaks in radiators, motor blocks, cylinder heads and freeze plugs
- Aluminium safe

• 21g





201 KLF



### **ENGINE SEAL**

- Stops minor oil leaks
- Revitalizes dried out and glazed rubber seals, gaskets and O-rings enabling them to reseal the engine
- For both diesel and gasoline engines
- 350 ml

# 702



201 KLF



### **COOLING SYSTEM SEALER & CONDITIONER**

- A homogenized liquid sealant designed to mix rapidly with radiator water/ glycol solutions, hot or cold, to rapidly seal leaking radiators, joints between head and block, hose connectors, etc
- 250 ml







### **BEARIN' SEAL**

 Stops minor oil leaks in front and rear main bearing seals, head gaskets and timing chain covers

• 350 ml



### **ENGINE STOP LEAK**

 Revitalizes oil seals and gaskets that have shrunk due to temperature or age, 100% petroleum product, compatible with all sealing and gasket materials

• 354 ml





### **BLOCK SEAL - LIQUID**

- Repairs cracked engine blocks, cylinder heads, valve parts, water jackets on all water-cooled engines
- Specially compounded engine block and cylinder head repair designed to form a rugged temperature-resistant bond
- 443 ml



# C501C

**SOLDER SEAL** 

 Stops leaks in radiators instantly and prevents

· Works in both water

**TOP LEAK - POWDER** 

new leaks from developing

and anti-freeze solutions



• 28.3 g

205 RAD





### LIQUID **RADIATOR REPAIR**

- Stops leaks in radiators and prevents new leaks from developing
- Works in water or anti-freeze solutions
- · Contains rust inhibitor
- · Will not harm metal, rubber hoses, gaskets
- 325 ml

# C312C



STEER-SEAL

steering units

350 ml

· Helps stop leaks and minimize noise and squealing in power

205 RAD



### **SUPER** RADIATOR SEALER

- Seals radiator leaks guickly without clogging system
- · Exclusive free-flowing non-clogging formula, seals larger leaks where others fail
- · Contains a rust inhibitor to retard formation of rust or corrosion
- Harmless to all metals, hoses, gaskets or any part of the cooling system
- 443 ml

# C2016C





205 RAD



**TRANSEAL** 

205 RAD

# MI7I2C



### **ELECTRIC MOTOR CONTACT CLEANER**

- A non-flammable, non-conducting cleaning solvent for alternators, generators, starters, contact relays and electric components
- 567 g

- · Designed to swell seals and provide additional high pressure lubrication
- Non-corrosive, clogging or foaming
- 350 ml

# MI512C



205 RAD





### **DUPONT™ SUVA® I34A REFRIGERANT**

- · Non-ozone depleting HFC refrigerant
- Also used in new medium and high-temperature stationary commercial refrigeration, as well as chiller systems and home appliances

# SUVAI34A

205

RAD







### **DUSTER®**

- Provides a powerful blast to remove dirt, dust and embedded debris
- Penetrates into minute cracks and crevices
- Non-flammable, safe on all plastics
- · 340 g aerosol with trigger



### **QD® CONTACT CLEANER**

- Ideal for cleaning sensitive electronics and electrical equipment
- No residue and safe on all plastics
- CFIA Approved
- 397 g



### **ELECTRONIC CLEANER**

- A petroleum distillate/alcohol based precision cleaner designed as an alternative to CFC based cleaners
- Ideal for applications where lower flashpoint materials can be tolerated
- 312 g

# 75102





### **LECTRA-MOTIVE® CLEANER**

- Air tools, alternators, battery chargers, bearings, cables, chains, clutches, compressors, dies, electric motors, generators, grinders, motor windings, motors, pumps, solenoids, starters, steel, tools, tools welders, wire rope
- Aerosol 539 g

CRC
LectraMotive

Netrical parts channel

Netsayant de pièce
disciplique
dis

# 75018



218 CRC

### **ELECTRONIC CLEANER**

- Suitable for cleaning sensitive electronics and electrical equipment
- Evaporates quickly, leaves no residue and is safe to use on all plastics
- Use where lower flashpoint cleaners are acceptable
- NSF K2 Registered.Telephones, PCs, relays, edge connectors, buss bars, circuits, contacts, printed circuit boards, switches & breakers
- 128 g



s bars, circuits,

# 75012



### **CLEAN-R-CARB® CARBURETOR** CLEANER

- Instantly dissolves deposits on venturis, linkages, butterflies and PCV systems to improve fuel system performance
- Harmless to catalytic converters and oxygen sensors
- 454 g





### **FUEL INJECTOR** CLEANER

- · Cleans dirty injectors to solve a wide range of engine problems: hard starts, rough idling, dieseling, engine run-on, knocks and pings
- 12 fl oz



# # 75061

### **SUPER TURBO® OCTANE BOOST**

- Increases horsepower & octane rating. and maximizes power & torque
- Protects against valve recession & replaces lubrication formerly found in leaded fuels
- Decreases NOX & carbon monoxide emissions
- Contains a smoke suppressant
- 355 ml





### **GUARANTEED TO PASS® EMISSIONS TEST FORMULA**

- Pass your emissions test or CRC will double your money back!
- · Powerful detergent additives super-clean the entire fuel system reducing emissions and improving performance
- Use every 3,000 miles to improve fuel economy, acceleration and reduce emissions
- 355 ml

# 75060-6 CRC 218

CRC



### **FUEL STABILIZER**

- Inhibits the formation of varnishes, peroxides & gums in gasoline, diesel fuel & aviation fuel during storage
- · 2-cycle, aviation fuel, diesel fuel, gasoline, turbine fuels
- 237 ml

# 75380 CRC 218 CRC



### SENSORKLEEN® MASS AIR FLOW SENSOR CLEANER

- Cleans mass air flow sensors
- · Plastic safe, dries in seconds
- 312 g

# 75110





### THROTTLE BODY KLEEN® AIR INTAKE CLEANER

- Cleans gum and varnish from the throttle valves and throttle body
- 340 g









### **POSI-TRAC® LIMITED SLIP GEAR OIL ADDITIVE**

- Posi-Trac Limited Slip Gear Oil Additive is designed to guiet chattering differentials and improve gear oil performance
- · Quiets noisy gears, mixes with any gear oil, inhibits foaming, and raises gear oil to GL-5
- 207 ml



# 742508



### **GUMOUT® FUEL INJECTOR** & CARBURETOR CLEANER

- Keeps fuel injectors and carburetors clean
- Restores lost horsepower
- · Safe for use in turbo & supercharged vehicles
- Helps reduce emissions
- Will not void OEM/manufacturer's warranty
- 177 ml



# 800001861



339 GUM



### **GUMOUT® REGANE®** HIGH MILEAGE FUEL SYSTEM CLEANER

For older vehicles that experience poor fuel economy, lost horsepower, hesitation, and rough idling.

- For vehicles over 75,000 miles
- · Cleans the ENTIRE fuel system
- Prevents deposit buildup
- Fights damaging effects of ethanol up to 15%
- Safe for use in turbo & supercharged vehicles
- · Will not void OEM/manufacturer's warranty
- 177 ml



# 800001742



339 **GUM** 

### **GUMOUT® DIESEL FUEL** INJECTOR CLEANER

- · Cleans direct & indirect fuel injectors, intake valves and ports
- · Keeps combustion chamber clean
- · Restores lost horsepower
- Formulation works with traditional diesel fuel as well as biodiesel fuel (up to B20)
- Safe in turbo & supercharged vehicles
- Helps reduce emissions
- Will not void OEM/manufacturer's warranty

# 800001738



### **GUMOUT® FUEL INJECTOR CLEANER**

For vehicles experiencing poor fuel economy, lost horsepower, hesitation, and rough idling.

- · Cleans fuel injectors, intake valves and ports
- Prevents future deposit buildup
- · Restores lost horsepower
- Safe in turbo & supercharged vehicles
- Helps reduce emissions
- Will not void OEM/manufacturer's warranty

# 800001739



339 GUM





### GUMOUT® REGANE® HIGH MILEAGE FUEL SYSTEM CLEANER

- Cleans the ENTIRE fuel system
- Maximizes fuel economy
- Prevents future deposit buildup
- Restores lost horsepower
- · Cleans gasoline direct injection (GDI) systems
- Fights damaging effects of ethanol up to 15%
- · Removes water from gasoline
- Safe for use in turbo & supercharged vehicles
- · Helps reduce emissions
- Will not void OEM/manufacturer's warranty
- 177 ml



# 800001743



339 GUM

# GUMOUT® OCTANE BOOSTER

- Octane stops knocks and pings, and provides maximum fuel economy and performance
- Safe for use in turbo & supercharged vehicles
- Will not void OEM/manufacturer's warranty
- 296 ml

# 800001860



339 GUM

# NOS® RACING FORMULA OCTANE BOOSTER

- Increase octane effect up to 7 points
- Eliminates knocks, pings and hesitation
- Meets BMW requirements for IVD detergency
- 355 ml



# 12012



### GUMOUT® GAS TREATMENT

For vehicles experiencing poor fuel economy, lost horsepower, and even fuel line freeze because of water in tank.

- Fights rust and corrosion
- Removes water to help reduce gas line freezing
- Safe for use in turbo & supercharged vehicles
- Will not void OEM/manufacturer's warranty
- 177 ml

# 800001740



# GUMOUT® FUEL SYSTEM CLEANER

- · Cleans fuel injectors, intake valves and ports
- Keeps combustion chamber clean
- · Prevents future deposit buildup
- Safe for use in turbo & supercharged vehicles
- Will not void OEM/manufacturer's warranty
- 177 ml

# 800002270



339 GUM

### **HEAVY DUTY RADIATOR CLEANER**

- Removes rust and scale from automotive engines, radiators and water jackets
- Cleans and unclogs steam cleaner coils and boiler tubes
- Not for use in aluminium radiators
- · I qt







# THORO-FLUSH INDUSTRIAL-STRENGTH RADIATOR AND ENGINE CLEANER

- Loosens and removes rust, scale, grease, oil, and sludge
- Cleans automotive and heavy duty truck cooling systems
- · Most powerful flush available

# 468-9112-16

### **ALL WEATHER SEAL**

- Ultimate fix for head gasket leaks
- · Seals intake gasket leaks and cracks in cylinder head and engine blocks
- Prevents anti-freeze seepage
- · Lubricates water pump seals
- · Mixes with all antifreeze

# 468-9132-16

### **CERAMIC SEAL**

- Permanently seals leaking head gaskets, cracked heads and blocks in aluminum or cast iron"
- Coats the engine and prevents formation of rust and corrosion
- Seals porous casting in the cooling system
- Stops coolant leaks







### **AUTOMATIC TRANSMISSION SUPPLEMENT (ATS)**

- Soluble molybdenum-fortified supplement with corrosion inhibitors and anti-foam agents
- Protects transmission components
- Blends with automatic transmission and power steering fluids, engine and gear oils
- 225 ml



417

MLY

# # 5932

### MOLYSLIP E – ENGINE OIL SUPPLEMENT

- Suspension of 0.5 micron particles of molybdenum disulfide (MoS2).
- Blends with all leading motor oils, including synthetics
- Will NOT clog oil filters or oil passageways
- · Ideal for both diesel and gasoline engines

#	Size	
3412	300 ml	
3415	ΙL	
3416	4 L	





MANUAL TRANSMISSION SUPPLEMENT (MTS)

• Suspension of molybdenum disulfide (MoS2) in

a high quality multi-viscosity gear oil with extreme pressure, anti-foam and adhesion additives

· Blends with all types of gear oils, including synthetic

and semi-synthetic and automatic transmission fluid

Ideal for manual transmissions, differentials and

**MOLYSLIP G -**









417 MLY

### AIR INTAKE SYSTEM CLEANER

- Specially formulated to clean, lubricate and prevent corrosion in throttle valves, throttle bodies and idle control valves
- 418 g





### **CARBURETOR CLEANER**

- Supplement to gasoline which quickly and effectively cleans carburetor jets
- Removes vanish and gum coating for improved flow and gasoline combustion
- 350ml

410 10	201
	KLF



# AUTOMATIC CHOKE & CARBURETOR CLEANER

- Contains special organic components for dissolving gum and varnish
- Recommended especially for cleaning valve and emission control units
- 404 g



# COMBUSTION CHAMBER CLEANER

- Designed for sluggish engines, purges carbon, gum, varnish, sludge from internal parts
- Helps increase gas and oil mileage, also peps up acceleration
- 475 g

	<del>.#</del>	82.
Hen 416	201	
	KLF	
7		



# TKO-TOTAL COMBUSTION OVERHAUL

- Professional set designed to knock out combustion chamber, intake valves and fuel injector deposits
- Restores engine performance, stops engine knock and run on, and restores smooth idling





### **TKO 2000**

- Concentrate that cleans up of fuel injector, intake valve and combustion chamber deposits
- Eliminates rough idling, hesitation, knock and ping
- · Methyl hydrate free
- 475 ml





### **DIESEL FUEL CONDITIONER**

- Removes varnish and sludge
- Reduces corrosion
- · Prevents stalling and frozen fuel lines
- Retards wax formation



Size
150 ml
500 ml
I L
4 L







### **LOW SULPHUR DIESEL FUEL CONDITIONER**

- · Helps restore lost lubrication from the use of low sulphur diesel fuels
- Absorbs moisture in fuel tank and prevents freezing and icing of fuel lines and filters
- | L



### LOW SULPHUR DIESEL FUEL ANTIGEL WITH CONDITIONER

- Restores lost lubrication to fuel injectors and pumps from the use of low sulphur diesel fuels
- Prevents gelling of fuel down to -45°C
- Absorbs moisture in fuel tank
- | |



### **EMISSION CONTROL CLEANER**

- · Reduces carbon monoxide, nitrous oxide and hydrocarbon emissions
- Removes carbon and gum deposits
- · One tank treatment good up to 5000 km
- 350 ml



### **ENGINE FLUSH**

- Fluid to flush engine before changing the oil
- Works in 5 minutes
- Cleans clogged screens
- Removes piston varnish and crankcase sludge
- 350ml






### **FUEL SYSTEM KLEEN**

- · Powerful formula to flush away gummy deposits that build up on the fuel injector tips, causing hesitation, poor fuel economy, uneven idling and stalling
- 340 g





DIESEL LUBRICANT

- · Provides superior lubricity and anti-wear protection, helps disperse water from the fuel
- Treats up to 3,000 litres





- Reduces gum and deposits on diesel fuel injectors, prevents fuel system corrosion, lubricates and protects injectors and pumps
- Does not contain methyl
- 350 ml





### **FUEL STABILIZER**

- · Keeps fuel fresh during extended storage for easier start next season
- · Good for all grades of gasoline, on 2-cycle and 4-cycle engines
- Ensures fuel stability for I year
- 350 ml





### INJECTOR KLEEN

- · Cleans and protects fuel injector systems
- Reduces gum and deposits on port injectors and pintles
- Methyl-hydrate free
- Oxygen sensor and catalytic converter safe
- 395 ml

	#	695
Hen	201	
	KLF	



### **GAS TREATMENT**

- · Helps maintain a clean combustion chamber, lubricate upper cylinder and prevent deposits



### **IGNITION SEALER**

- · Protects against shorts in all automotive and electrical connections
- 170 g





### LEAD SUPPLEMENT **OCTANE BOOSTER**

- Gasoline additive formulated to protect against valve seat wear in engines designed for leaded fuel
- Supplements octane level in the fuel
- · Sustains high performance, fuel economy
- 350 ml



### **OIL SUPPLEMENT**


- · Protects against excessive engine wear caused by dry starts
- · Compatible with diesel and gasoline engine oils
- 350 ml





### **OIL TREATMENT**

- · Synthetic crankcase oil additive designed to treat oil burning, exhaust smoking, low oil pressure, noisy engines and low engine compression
- · Protects against corrosion
- · Recommended for diesel and gasoline engines
- 325ml





- Designed to remove rust deposits, lime, gasket cement, greasy sludge and scale from cooling systems
- · Aluminum compatible
- 450 ml





20 I KLF





### **AUTOMATIC TRANSMISSION SEALER** & CONDITIONER

- Stops fluid leaks
- Removes surface glaze and revitalizes rubber seals
- 350 ml



20 I KLF

### **KLEEN VALVES AND LIFTERS**

- · Added to the crankcase, rapidly dissolves the oil varnish on valves and in lifters
- · Designed for both gasoline and diesel engines
- 325 ml

700 201 KLF



### **FUEL STABILIZER**

- Prevents gasoline break-down during storage
- · Safe to use in all grades of gasoline
- · I ounce will treat I gallon

_	
#	Size
20302	15 oz
20314	8 oz



277 LUC

### **FUEL TREATMENT**

- Formulated for both gasoline and diesel engines, carbureted or fuel injected. Use it to pass smog tests
- Cleans and lubricates the fuel system
- Neutralizes low sulfur fuel problems
- Burns excess exhaust emissions
- · Increases the life of pumps and injectors

#	Size
20003	l quart
20013	l gallon
20020	5.25 oz
277	



LUC



### WATER PUMP LUBRICANT & RUST INHIBITOR

- Revives the rust protective agents of anti-freeze and lubricates the water pump
- Aluminium compatible
- 450 ml

# 709 201 KLF



### **BIO MEDIC® FUEL STERILIZER**

- · Controls biological and organic growth in diesel fuel
- · Sterilize infected fuel
- · Coats the fuel tank with a film of lubricant further reducing the growth environment
- · An economical alternative to centrifuge technology
- · I quart treats 250 gallons of fuel





### TRANSMISSION FIX

- Non-solvent formula that stops slip, hesitation and rough shifting in worn transmissions
- · Completely eliminates most seal leak





LUC